



CATALOG

DESIGNED AND DEVELOPED IN **THE NETHERLANDS** 



CORDLESS LI-ION SCREWDRIVER 3.6V - 1.3AH CDM1132 Specifications Mains voltage (charger) 100-240V~, 50/60Hz Power input Max. torque No load speed Charging time 3.6V-1.3AH 4Nm 230/min 3-5 hours Features - Cordless, Li-ion technology - Spindle lock - LED work light - Magnetic chuck 1/4" - Metal storage case  Includes 27 pcs accessory set - Charger adapter	CORDLESS LI-ION DRILL 12V - 1.5AH CDM1119 Specifications Mains voltage (charger) 100-240V~, 50/60Hz Power input Max. torque (hard) No load speed position I No load speed position II Number of torque positions Charging time 12V-1.5Ah 20Nm 0-350/min. 0-1.300/min. 17+1 1 hour Features - Cordless, Li-Ion technology - 2 Batteries - LED work light - Single sleeve chuck 1.0-10mm - Adjustable torque settings - Two mechanical speed settings - Variable electronic speed control - Storage case  Includes 2 Li-Ion batteries (12V-1.5Ah) - 2 Double sided 50mm bits (S2) - Charger Optional Accessories Bit set CDA1035 - Battery CDA1085	IMPACT DRILL 800W PDM1052 Specifications Mains voltage Power input No load speed No load impact rate Chuck capacity 230V~, 50Hz 800W 0-3.000/min. 0-48.000/min. 2-13mm Features - Double function (drilling and impact drilling) - Depth limiter - Variable electronic speed control - Lock-on switch - 3m rubber cable  Includes Side handle - Depth limiter	ROTARY HAMMER 850W HDM1028 Specifications Mains voltage Power input No load speed No load impact rate Impact energy Chuck size 230-240V~, 50/60Hz 850W 900/min. 4.000/min. 4.5 Joule SDS-plus Features - 3 Functions (dilling, hammer drilling, chiseling) - Universal SDS-plus toolholder - 3m cable - Storage case  Includes Side handle - Dust cover - Grease tube - Depth gauge - 3 SDS concrete drills (8mm, 10mm, 12mm) - Chisel pointed (250mm) - Chisel flat (250mm) - Grease cover - Wrench
CORDLESS LI-ION DRILL 18V - 1.5AH CDM1131 Specifications Mains voltage (charger) 100-240V~, 50/60Hz Power input Max. torque (hard) No load speed position I No load speed position II Number of torque positions Charging time 18V-1.5Ah 32Nm 0-350/min. 0-1.300/min. 17+1 1 hour Features - Cordless, Li-Ion technology - LED work light - Single sleeve chuck 1.5-13mm - Adjustable torque settings - Two mechanical speed settings - Variable electronic speed control - Storage case  Includes 1 Li-Ion batteries (18V-1.5Ah) - 2 Double sided 50mm bits (S2) - Charger Optional Accessories Bit set CDA1035 - Battery CDA1087	CORDLESS LI-ION DRILL 18V - 1.5AH CDM1120 Specifications Mains voltage (charger) 100-240V~, 50/60Hz Power input Max. torque (hard) No load speed position I No load speed position II Number of torque positions Charging time 18V-1.5Ah 32Nm 0-350/min. 0-1.300/min. 17+1 1 hour Features - Cordless, Li-Ion technology - 2 Batteries - LED work light - Single sleeve chuck 1.5-13mm - Adjustable torque settings - Two mechanical speed settings - Variable electronic speed control - Storage case  Includes 2 Li-Ion batteries (18V-1.5Ah) - 2 Double sided 50mm bits (S2) - Charger Optional Accessories Bit set CDA1035 - Battery CDA1087	ROTARY HAMMER 1500W HDM1037 Specifications Mains voltage Power input No load speed No load impact rate Impact energy Chuck size 230V~, 50Hz 1.500W 0-950/min. 0-4.400/min. 6.0 Joule SDS-plus Features - 4 Functions (drilling, hammer drilling, free rotation chiseling, chiseling) - Universal SDS-plus toolholder - Variable electronic speed control - 3m cable - Storage case  Includes Side handle - Dust cover - Grease tube - Depth gauge - 3 SDS concrete drills (8mm, 10mm, 12mm) - Chisel pointed (250mm) - Chisel flat (250mm) - Grease cover - Wrench	ANGLE GRINDER 500W - 115MM AGM1086 Specifications Mains voltage Power input No load speed Disc diameter Spindle 230V~, 50Hz 500W 11.000/min. 115mm M14 Features - Lock-on switch - Spindle lock - Adjustable open safety guard - Electronic restart protection - 3m cable  Includes Side handle - Wrench - Hexagonal key Optional Accessories Diamond disc 115mm AGA1018 (open) - AGA1020 (closed)
CORDLESS LI-ION IMPACT WRENCH 18V - 4.0AH CDM1127 Specifications Mains voltage (charger) 100-240V~, 50/60Hz Power input Max torque No load speed Charging time 18V-4.0Ah 380Nm 0-2.300/min. 3-5 hours Features - Cordless, Li-Ion technology - ½" square drive shaft - LED work light - Variable electronic speed - Soft grip - Storage case  Includes Li-Ion battery (18V-4.0Ah) - Socket 19mm - Socket 21mm - Charger	IMPACT DRILL 550W PDM1051 Specifications Mains voltage Power input No load speed No load impact rate Chuck capacity 220-240V~, 50Hz 550W 0-3.000/min. 0-48.000/min. 2-13mm Features - Double function (drilling and impact drilling) - Depth limiter - Variable electronic speed control - Lock-on switch - 3m rubber cable  Includes Side handle - Depth limiter	ANGLE GRINDER 750W - 115MM AGM1060S Specifications Mains voltage Power input No load speed Disc diameter Spindle 230-240V~, 50Hz 750W 12.000/min. 115mm M14 Features - Paddle switch - 3 Side handle positions - Spindle lock - Adjustable open safety guard with quick release - 3m rubber cable  Includes Side handle - Wrench Optional Accessories Diamond disc 115mm AGA1018 (open) - AGA1020 (closed)	ANGLE GRINDER 850W - 125MM AGM1087 Specifications Mains voltage Power input No load speed Disc diameter Spindle 230V~, 50Hz 850W 11.000/min. 125mm M14 Features - Lock-on switch - Spindle lock - Adjustable open safety guard - Electronic restart protection - 3m cable  Includes Side handle - Wrench - Hexagonal key Optional Accessories Diamond disc 115mm AGA1019 (open) - AGA1021 (closed)

ANGLE GRINDER 900W - 125MM AGM1061S Specifications Mains voltage 230-240V~, 50Hz Power input 900W No load speed 12.000/min. Disc diameter 125mm Spindle M14 Features - Paddle switch - 3 Side handle positions - Spindle lock - Adjustable open safety guard with quick release - 3m rubber cable Includes Side handle - Wrench Optional Accessories Diamond disc 115mm AGA1019 (open) - AGA1021 (closed) 	ANGLE GRINDER 2500W - 230MM AGM1088 Specifications Mains voltage 230-240V~, 50Hz Power input 2.500W No load speed 6.500/min. Disc diameter 230mm Spindle M14 Features - Lock-off safety switch - Spindle lock - Adjustable open safety guard - Soft start - 3 Side handle positions - 3m rubber cable Includes Side handle - Wrench - Hexagonal key 	PRECISION CIRCULAR SAW 500W CSM1043 Specifications Mains voltage 220-240V~, 50Hz Input power 500W No load speed 3.500-6.500/min. Saw blade diameter 85mm Saw blade bore 15mm Cutting depth 0-22mm Features - Variable speed - Adjustable sawing depth - 3pcs saw blade set included - Side handle - Dust extraction outlet - 3m rubber cable - Storage case Includes TCT saw blade T24 - HSS saw blade T44 - Diamond saw blade - Dust extraction adapter - Hexagonal key - Guide ruler - Handle Optional Accessories Precision saw blade CSA1046 - CSA1047 (24T-TCT) - CSA1048 (44T-HSS) - CSA1049 Guide rail set 	CIRCULAR SAW 1200W - 185MM CSM1039 Specifications Mains voltage 230-240V~, 50Hz Input power 1.200W Bevel adjustment 0-45° No load speed 5.000/min. Saw blade diameter 185mm Saw blade bore 20mm Cutting depth max. 65mm (90°) Cutting depth max. 43mm (45°) Features - Angle and depth adjustment - Parallel guide - Spindle lock - 3m rubber cable Includes Hexagonal key - Parallel guide - TCT saw blade 185mm T24 Optional Accessories Saw blade CSA1007 (T24) 
CORDLESS LI-ION JIG SAW 12V - 1.5AH JSM1026 Specifications Mains voltage (charger) 100-240V~, 50/60Hz Power input 12V-1.5Ah No load speed 2.100/min. Charging time 3-5 hours Features - Cordless, Li-Ion technology - Quick release blade holder - Universal, suitable for T & U shank blades - Soft grip - Storage case Includes Li-Ion battery (12V-1.5Ah) - Saw blade (wood) - Saw blade (metal) - Charger Optional Accessories Battery CDA1094 - Jig saw blades 10pcs JSA1004 	JIG SAW 570W JSM1023 Specifications Mains voltage 230V~, 50Hz Input power 570W No load speed 500-3.000/min. Bevel adjustment 0-45° Saw stroke 18mm Saw capacity wood max. 70mm Saw capacity steel max. 6mm Features - Lock-on switch - Electronic variable speed - 4 Pendulum positions - Variable mitre cut adjustment to 45° - Dust extraction outlet - 3m cable Includes Parallel guide - Hexagonal key - Vacuum cleaner adapter - 4 T-shank saw blades Optional Accessories Jig saw blades 10pcs JSA1004 	WALL SLOTTER 1700W - 125MM WSM1009 Specifications Mains voltage 230-240V~, 50Hz Input power 1.700W No load speed 4.000/min. Cutting depth 0-28mm Cutting width 14-19-29mm Disc diameter 125mm Features - Overload protection - Soft start - Spindle lock - Laser guidance - Adjustable cutting depth and width - 3m cable - Storage case Includes 2 Diamond discs - Universal vacuum cleaner adapter - Chisel - Hexagonal key - Batteries for laser Optional Accessories Saw blade set 2pcs WSA1001 (125mm open) 	WALL SLOTTER 1600W - 150MM WSM1008 Specifications Mains voltage 230V~, 50Hz Input power 1.600W No load speed 6.000/min. Cutting depth 8-40mm Cutting width 8-30mm Disc diameter 150mm Features - Overload protection - Soft start - Power feedback - Spindle lock - Laser guidance - Adjustable cutting depth and width - 3m cable - Canvas storage bag Includes 2 Diamond discs - Universal vacuum cleaner adapter - Chisel - Batteries for laser Optional Accessories Saw blade set 2pcs WSA1002 (150mm open) 
JIG SAW 710W JSM1014 Specifications Mains voltage 230V~, 50Hz Input power 710W No load speed 800-3.000/min. Bevel adjustment 0-45° Saw stroke 20mm Saw capacity wood max. 110mm Saw capacity steel max. 10mm Features - Lock-on switch - Electronic variable speed - 4 Pendulum positions - Variable mitre cut adjustment to 45° - Dust extraction outlet - 3m cable Includes Parallel guide - Hexagonal key - Vacuum cleaner adapter - 3 T-shank saw blades Optional Accessories Jig saw blades 10pcs JSA1004 	RECIPROCATING SAW 710W RSM1019 Specifications Mains voltage 230-240V~, 50Hz Input power 710W No load speed 0-2.800/min. Saw stroke 20mm Features - Lock-on switch - Electronic variable speed - Toolless saw blade release - Adjustable front plate - 3m rubber cable Includes Hexagonal key - 2 Saw blades Optional Accessories Reciprocating blades 9pcs RSA1001 	PAINT/CEMENT MIXER 1400W PMM1006 Specifications Mains voltage 230V~, 50Hz Input power 1.400W No load speed (I) 180-380/min. No load speed (II) 300-650/min. Features - Lock-on switch - Variable electronic speed control - Two mechanical speed settings - Whisk included - 3m rubber cable Includes Whisk for general purposes - 2 Wrenches Optional Accessories Whisk PMA1004 	DETAIL SANDER 220W PSM1013 Specifications Mains voltage 230V~, 50Hz Input power 220W No load speed 13.000/min. Sanding movements 26.000/min. Sanding paper size 145x145x88mm triangle shape Features - Velcro base plate - Active dust extraction - 3m cable - Storage case Includes 5 Sanding papers (P80) - 5 Sanding papers (P120) - Dust bag Optional Accessories Sanding paper set 5pcs PSA1007 (P80) - PSA1008 (P120) 

ORBITAL SANDER 135W PSM1027 Specifications Mains voltage230V~, 50Hz Input power135W No load speed13.000/min. Sanding surface90x187mm  Features - Velcro ®base plate - Paper clamping system - Universal vacuum cleaner adapter - 3m rubber cable  IncludesSanding paper (P80) - Vacuum cleaner adapter Optional Accessories	ORBITAL SANDER 180W PSM1024 Specifications Mains voltage230V~, 50Hz Input power180W No load speed12.000/min. Sanding movements24.000/min. Sanding surface90x187mm  Features - Aluminum Velcro ®base plate - Paper clamping system - Universal vacuum cleaner adapter - 3m cable  Includes5 Sanding papers (P80) - 5 Sanding papers (P120) - Vacuum cleaner adapter Optional AccessoriesSanding paper set 5pcs PSA1031 P60 P80 P120	BELT SANDER 950W BSM1021 Specifications Mains voltage230V~, 50Hz Input power950W Belt dimension76x533mm Sanding surface76x135mm Belt speed220-350m/min.  Features - Dual function for both manual and stationary use - Electronic variable speed - Quick release belt exchange - 3m cable  IncludesDust bag - Sanding paper (P60) - Sanding paper (P80) - Sanding paper (P120) - 2 Stationary clamps - Rubber sheet Optional AccessoriesSanding belt set 3pcs P60, P80, P120 (BSA1013)	PLANER 650W PPM1010 Specifications Mains voltage230V~, 50Hz Input power650W No load speed16.500/min. Max. planing width82mm Max. planing depth max2mm  Features - Lock-on switch - Adjustable planing depth - Reversible hard metal planing knives - 3m cable  IncludesParallel guide - Spare belt - Dust bag Optional AccessoriesChisel set 2pcs 82mm PPA1003
DELTA SANDER 280W DSM1009 Specifications Mains voltage230-240V~, 50Hz Input power280W No load speed6.000-11.000/min. Sanding movements12.000-22.000/min. Sanding surface90x90x90mm  Features - Velcro ®base plate - Electronic variable speed - Universal vacuum cleaner adapter - 3m cable  Includes2 Sanding papers (P80 / wood) - 2 Sanding papers (P80 / paint) - 2 Sanding papers (P80 / stone) - Vacuum cleaner adapter - Protection cover for sanding pad nose Optional AccessoriesSanding paper set 10pcs PSA1033 (P80) - PSA1034 (P120)	RANDOM ORBITAL SANDER 430W ESM1010 Specifications Mains voltage230-240V~, 50Hz Input power430W No load speed5.000-13.000/min. Base plate diameter125mm  Features - Velcro ®base plate - Electronic variable speed - 3m cable  IncludesDust collection box - 2 Sanding papers (P60) - 2 Sanding papers (P80) - 2 Sanding papers (P120) Optional Accessories	PRECISION ROUTER 1200W PRM1021 Specifications Mains voltage230-240V~, 50Hz Power input1200W No load speed9.000-30.000/min. Max. cutting depth50mm Max. cutter diameter32mm  Features - Depth adjustment - Electronic variable speed control - Dust extraction connector - Spindle lock - 3m cable  IncludesParallel guide - Centring pin - Template guide - Spanner - 3pcs bit set - 6mm+8mm collet Optional AccessoriesRouter bit set 20pcs PRA1008 - Router table PRA1011	PRECISION ROUTER 1300W PRM1015 Specifications Mains voltage230V~, 50Hz Power input1300W No load speed9.000-30.000/min. Max. cutting depth60mm Max. cutter diameter30mm  Features - Accurate depth adjustment: 0.1mm - Electronic variable speed control - LED work light - Lock-off switch in handle - Dust extraction connector - Spindle lock - 3m cable  IncludesParallel guide - Template guide - Wrench - Hexagonal key - 6pcs bit set - 6mm+8mm collet Optional AccessoriesRouter bit set 20pcs PRA1008 - Router table PRA1011
PRECISION BELT SANDER 400W EFM1001 Specifications Mains voltage230-240V~, 50Hz Input power400W No load speed1.070-1.650/min. Belt length455mm Belt width8 and 13mm  Features - Electronic variable speed - Quick release belt exchange - 3m cable - Storage case  IncludesDust bag - Vacuum cleaner adapter - 3 Sanding arm (8mm, 13mm, 13mm angled) - 12 Sanding papers Optional AccessoriesSanding belt set 8pcs P40, P80, P120 EFA1003 (10mm) - EFA1004 (13mm)	BELT SANDER 950W BSM1024 Specifications Mains voltage230V~, 50Hz Input power950W Belt dimension75x533mm Sanding surface75x135mm Belt speed380m/min.  Features - Electronic variable speed - Quick release belt exchange - 3m cable  IncludesSanding belt (P80) - Dust bag Optional AccessoriesSanding belt set 3pcs P60, P80, P120 (BSA1013)	ROUTER TABLE PRA1011 Specifications Mains voltage230V~, 50Hz Table size455x330mm Max. base plate diameter router162mm  Features - Safety switch - Dust extraction port - Adjustment plate - Robust and stable aluminum construction, provided with rubber feet - Fits all current FERMI routers and most other routers  IncludesFence - Featherboard - Vacuum cleaner adapter Optional Accessories	PRECISION BISCUIT JOINTER 900W BJM1009 Specifications Mains voltage230V~, 50Hz Input power900W No load speed11.000/min. Saw blade100x22mm Saw blade thickness4mm Cutting depth0-14mm Base adjustment0°-90° Biscuits size0-10-20  Features - For creating precise joints and sawing parquet along walls - Easy adjustment for angle and material thickness - Aluminum base plate - Spindle lock function - Storage case  IncludesSaw blade 100x22x4mm - Hexagon key - Dustbag - 50 Biscuits (#20) Optional AccessoriesBiscuits 50pcs 56x23x4mm BJA1004 - Saw blade BJA1005

CORDLESS LI-ION MULTI TOOL 12V - 1.5AH OTM1006 Specifications Mains voltage (charger) 100-240V~, 50/60Hz Power input 12V-1.5Ah No load speed 5.000-18.000/min. Oscillation angle 3.0° Charging time 3-5 hours  Features - Cordless, Li-Ion technology - Universal blade connection - Electronic variable speed - Easy blade exchange - Soft grip - Storage case Includes Li-Ion battery (12V-1.5Ah) - 3 Sanding papers - Velcro® sanding base plate - HSS half round cutting blade - Plunge cutting blade - Scraping knife - Hexagon key Optional Accessories Battery CDA1094 - Plunge cutting blade OTA1001 - Scraping knife OTA1002 - Sanding pad OTA1003 - HSS segment saw blade OTA1004 - Carbide blade OTA1005	MULTI TOOL 280W OTM1005 Specifications Mains voltage 230V~, 50Hz Input power 280W No load speed 11.000-20.000/min. Oscillating angle 2.8°  Features - Lock-on switch - LED work light - Universal vacuum cleaner adapter - Electronic variable speed - Easy blade exchange - 3m cable - Storage case Includes Vacuum cleaner adapter - 10 Sanding papers - Velcro® sanding base plate - HSS half round cutting blade - Plunge cutting blade - Scraping knife - Carbide saw blade - Hexagon key Optional Accessoires Plunge cutting blade OTA1001 - Scraping knife OTA1002 - Sanding pad OTA1003 - HSS segment saw blade OTA1004 - Carbide blade OTA1005	ELECTRIC BLOWER 400W EBM1003 Specifications Mains voltage 220-240V~, 50Hz Input power 400W No load speed 6.000-14.000/min Max. air displacement 3.0m³/min Blow pipe size 220x25mm  Features - Lock-on switch - Electronic variable speed - Use as blower and vacuumcleaner - 3m cable Includes Rubber blow pipe - Dust bag	CORDLESS LI-ION ELECTRIC TACKER 3.6V - 1.5AH ETM1005 Specifications Mains voltage (charger) 100-240V~, 50/60Hz Power input 3.6V - 1.5Ah Staple width 11.3mm (type 530) Staple length 6-12mm Max. staple speed 30pcs/min. Charging time 1 hour  Features - Cordless, Li-Ion technology - Max. staple size 12mm - LED work light - 100pcs max. capacity - Soft grip - USB charger - Storage case Includes 1000 Staples 6mm - 1000 Staples 12mm - Charger - USB charge cable Optional Accessories Staples 2000pcs ETA1009 (8mm)
CORDLESS LI-ION COMBITOOL 12V - 1.5AH CTM1016 Specifications Mains voltage (charger) 100-240V~, 50/60Hz Power input 12V-1.5Ah No load speed 3.000-20.000/min. Charging time 3-5 hours  Features - Cordless, Li-Ion technology - Electronic variable speed - Suitable for 2.4mm and 3.2mm accessories - Soft grip - Spindle lock - Storage case Includes 1 Li-Ion battery (12V-1.5Ah) - 43 Accessories - Collet Ø2.4mm - Collet Ø3.2mm - Wrench - Charger Optional Accessories Battery CDA1094 - Combitool set 100pcs CTA1007 - Combitool set 40pcs CTA1008	COMBITOOL 160W CTM1012 Specifications Mains voltage 230V~, 50Hz Input power 160W No load speed 15.000-35.000/min. Collet diameter 2.4 and 3.2mm  Features - Electronic variable speed - Spindle lock - 3m cable - Storage case Includes 40 Accessories - Collet Ø2.4mm - Collet Ø3.2mm - Wrench Optional Accessories Combitool set 100pcs CTA1007 - Combitool set 40pcs CTA1008	ELECTRIC TACKER MAX. 16MM ETM1004 Specifications Mains voltage 230V~, 50Hz Staple width 11.3mm Staple length 8-16mm Nail length 15-16mm  Features - Impact control wheel - Anti-jam mechanism - Compact design - Safety switch Includes 400 Staples 14mm - 100 nails 15mm Optional Accessories Nails 1500pcs ETA1005 (15mm) - Staples 2000pcs ETA1009 (8mm) - Staples 2000pcs ETA1010 (14mm)	CORDLESS LI-ION GLUE GUN 7.2V - 1.5AH GGM1003 Specifications Mains voltage (charger) 100-240V~, 50/60Hz Power input 7.2V-1.5Ah Runtime on 1 charge: 45min. Charging time 1 hour Glue stick size Ø7mm  Features - Cordless, Li-Ion technology - Fast: 15s pre-heat time - 170° C work temp. - Automatic stop (after 5 minutes of inactivity) - Soft grip - Storage case Includes 6 Glue sticks GGA1003 (7x150mm)
COMBITOOL SET 160W CTM1010 Specifications Mains voltage 230V~, 50Hz Input power 160W No load speed 15.000-35.000/min. Collet diameter 2.4 and 3.2mm  Features - Electronic variable speed - Spindle lock - 3m cable - Flexible shaft - Adjustable stand - Desk stand - Storage case Includes 40 Accessories - Collet Ø2.4mm - Collet Ø3.2mm -Wrench Optional Accessories Combitool set 100pcs CTA1007 - Combitool set 40pcs CTA1008	HOT AIR GUN 2000W HAM1015 Specifications Mains voltage 220-240V~, 50Hz Input power 2.000W Pos. I: 300 L/min. 450°C Pos. II: 500 L/min. 600°C  Features - Overheat protection - Stationairy mode - 2 Heat and air flow settings - 3m cable - Storage case Includes Fishtail diffuser - Deflector diffuser	GLUE GUN 75W GGM1004 Specifications Mains voltage 220-240V~, 50Hz Rated power 25W Max. power 75W Glue stick diameter 11.2mm Heat-up time 3-5 min Glue flow 8-12g/min  Features - Adjustable table stand - Anti-drip control - Insulated nozzle - Protection side lifts Includes 4 Glue sticks 150mm Optional accessories 6 Glue sticks GGA1005 (11.2x100mm)	SOLDERING STATION 48W SGM1013 Specifications Mains voltage 220-240V~, 50Hz Input power 48W Temperature 160°C - 480°C  Features - Adjustable temperature - Accessory drawer - Overheat protection - Mica heating element - Replaceable tips - Soft grip on bolt Includes Flat tip - Point tip - Sponge - Solder wire Ø1.0mm - Solder wire Ø1.5mm

Specifications

Runtime on single fill	35min.
Max. flame temperature	1300°C
Max. soldering temperature	500°C

- For precise soldering, shrinking, hot cutting, lighting your fireplace, for kitchen use etc.
- Suitable for standard lighter gas
- Storage case

A handheld plasma torch with a blue handle and a black grip. The torch is emitting a bright blue flame from its tip. The handle has some text and a logo, including the word "FUSION" and a circular logo with a stylized 'F'.

Specifications

Mains voltage	220-240V~, 50Hz
Input power	110W
Max flow	300ml/min.
Container	800ml

- Adjustable flow control
- Easy cleaning
- Airless spray
- 3m cable

A black and blue electric spray gun with a white container. The brand name "FERM" is visible on the black body. It has a trigger handle and a spray nozzle.

Specifications

Mains voltage	230V~, 50Hz
Input power	350W
Chuck capacity	13mm
Taper of spindle	B16
No load speed	500-890-1.400-

- Cast iron base for maximum stability
- Key chuck (13mm)
- In height adjustable working table with two way angle adjustment from 0° to 45°
- Safety switch

A blue and black manual sprayer machine with two spray nozzles attached by a hose. The brand name "FERM" is visible on the top and side. It has a pump handle and various adjustment knobs.

Specifications

Mains voltage	230V~, 50Hz
Input power	150W
Grinding stone dimensions	150x16mm
Grinding stone grain	P36 & P60
Grinding stone bore	12.7mm
No load speed	2.950/min.

- Dust protected switch
- Metal base
- Mountable to work bench

Specifications	
Mains voltage	230V~, 50Hz
Input power	250W
Grinding stone dimensions	150x20mm
	150x40mm
Grinding stone grain	P36 (grey) P80 (white)
Grinding stone bore	12.7mm
No load speed	2.950/min.

- Dust protected switch
- Metal base
- Mountable to work bench

Specifications	
Mains voltage	230V~, 50Hz
Input power	250W
Grinding stone dimensions	150x20mm 200x40mm
Grinding stone grain	P36 (dry) P80 (wet)
Grinding stone bore	12.7mm(dry) 20mm (wet)
No load speed	2.950/min(dry) 135/min(wet)

- Dust protected switch
- Metal base
- Mountable to work bench



Specifications

Mains voltage	230-240V~, 50Hz
Input power	350W
Belt dimension	100x915mm
Disc diameter	150mm
Belt speed	292m/min.
Disc speed	1.450/min.
Belt position adjustable	0°-90°
Table position adjustable	0°-45°

- Velcro® disc base
- Dust protected safety switch
- Adjustable sanding belt position
- Adjustable working table
- Quick release belt exchange
- Rubber feet
- 2pcs 32mm 90° vacuum cleaner adapters

Specifications	
Mains voltage	230-240V~, 50Hz
Power input	1.300W
No load speed	4.500/min.
	Max. saw capacity
Mitre 0°, bevel 0°	55x120mm
Mitre 0°, bevel 45°	32x120mm
Mitre 45°, bevel 0°	55x80mm
Mitre 45°, bevel 45°	32x80mm

- Metal base plate
- Sliding fence
- Laser guidance
- Transparent saw blade cover
- Mountable to workbench
- Toolless mitre and bevel adjustment
- Extension bars

Specifications	
Mains voltage	230V~, 50Hz
Power input	1.900W
No load speed	4.800/min.
	Max. saw capacity
Mitre 0°, bevel 0°	70x310mm
Mitre 0°, bevel 45°	40x310mm
Mitre 45°, bevel 0°	70x210mm
Mitre 45°, bevel 45°	40x210mm

- Metal base plate
- Sliding fence
- Laser guidance
- Transparent saw blade cover
- Mountable to workbench
- Pre-settings for quick and accurate mitre-angle adjustment
- Extension bars

Specifications

Mains voltage	230V~, 50Hz
Input power	120W
Bevel adjustment table	0-45°
Max. working depth	406mm
Max. Sawing capacity at 90°	50mm
Max. Sawing capacity at 45°	23mm
No load speed	400 - 1600/min


- Safety switch
- Foot pedal switch
- Adjustable speed
- Quick blade tensioning
- Transparent guard
- Working table adjustable from 0-45°
- Flexible dust blower
- Vacuum cleaner connection
- Rubber feet

A blue and black manual grinding machine, branded 'FERMAT', is shown. It features a large black grinding wheel mounted on a blue frame. A clear plastic safety guard is positioned over the wheel. A black foot pedal is connected to the machine via a power cord. The machine is designed for manual operation and is typically used for grinding and polishing various materials.

Specifications	
Mains voltage	230V~, 50Hz
Power input	1.900W
No load speed	4.800/min.
	Max. saw capacity
Mitre 0°, bevel 0°	60x310mm
Mitre 0°, bevel 45°	35x310mm
Mitre 45°, bevel 0°	60x210mm
Mitre 45°, bevel 45°	35x210mm

- Metal base plate
- Sliding fence
- Laser guidance
- Transparent saw blade cover
- Mountable to workbench
- Pre-settings for quick and accurate mitre-angle adjustment
- Extension bars

capacity
10mm
10mm
10mm
10mm



Specifications	
Mains voltage	230V~, 50Hz
Input power	800W
No load speed	2.950/min.
Table size	500x355mm
Saw blade diameter	200mm
Saw blade bore	16mm
Cutting capacity max.	45mm (bevel 0°)
Cutting capacity max.	27mm (bevel 45°)

- Safety switch
- Induction motor
- Adjustable table 0-45°
- Mountable to workbench
- Parallel/mitre guide and clear scale
- 2m cable



TABLE SAW 1500W - 210MM TSM1035 Specifications Mains voltage 220-240V~, 50Hz Input power 1.500W No load speed 5.000/min. Saw blade adjustment 0-45° Max. cutting capacity 0° 70mm - 45° 45mm Saw blade diameter 210mm Table height 800mm Table size (with extensions) 676x500mm Features - Safety switch - Overload protection - Dust extraction - Durable steel table with table extensions - Height adjustable saw blade - Angle adjustable saw blade Includes TCT saw blade 210x30mm T24 - Wrench - Hexagonal key - Mitre guide - Parallel guide - Push stick - 4 rubber feet - 2 tilt prevention frames Optional Accessories Saw blade 210mm MSA1024 (24T) - MSA1025 (40T)	TABLE SAW 1800W - 250MM TSM1033 Specifications Mains voltage 230-240V~, 50Hz Input power 1.800W No load speed 4.700/min. Saw blade adjustment 0-45° Max. cutting capacity 0° 74mm - 45° 63mm Saw blade diameter 250mm Table height 865mm Table size (fully extended) 930x625mm Features - Safety switch - Overload protection - Dust extraction - Extendable aluminum table top - Height adjustable saw blade - Angle adjustable saw blade Includes TCT saw blade 250x30mm T40 - Wrench - Hexagonal key - Mitre guide - Parallel guide - Push stick - 4 rubber feet - 2 tilt prevention frames - Safety glasses - Ear plugs Optional Accessories Saw blade 250mm MSA1026 (40T) - MSA1027 (72T)	BATTERY CHARGER 6V / 12V BCM1021 Specifications Mains voltage 230V~, 50Hz Power Input Max. 110W Battery capacity Min. 20Ah Max. 75Ah Features - Ampere meter - 6/12V charging Includes Set battery clamps - 10A fuse	BATTERY CHARGER 6V / 12V BCM1020 Specifications Mains voltage 230V~, 50Hz Power Input Max. 400W Fast charge 12V DC, 12A 100S 6A 180S Normal charge 6/12V DC, 2A Features - Transport handle - Fast and normal charge - Deep cycle - LCD display and indicator - Reverse polarity, short circuit and overload protection - Recharge of drained batteries Includes Set battery clamps - 80A fuse
TILE CUTTER 600W - 180MM TCM1010 Specifications Mains voltage 230V~, 50Hz Input power 600W No load speed 2.950/min. Table adjustment 0-45° Table size 360x330mm Disc diameter 180mm Saw blade bore 22.2mm Features - Safety switch - Adjustable table from 0-45° - Durable chrome plated table - Parallel / mitre guide - Low noise induction motor - Water cooling - Mountable to workbench Includes Diamond saw blade 180x22.2mm - Wrench - Parallel guide - Water tray - Safety glasses - Ear plugs Optional Accessories Diamond disc 180mm TCA1004	TILE CUTTER 900W - 200MM TCM1011 Specifications Mains voltage 230V~, 50Hz Input power 900W No load speed 2.950/min. Table adjustment 0-45° Table size 500x400mm Disc diameter 200mm Saw blade bore 25.4mm Features - Safety switch - Adjustable table from 0-45° - Durable chrome plated table - Parallel / mitre guide - Low noise induction motor - Water cooling - Mountable to workbench Includes Diamond saw blade 200x25.4mm - Wrench - Parallel guide - Water tray - Safety glasses - Ear plugs Optional Accessories Diamond disc 200mm TCA1005	BOTTLE JACK MAX. 2000KG JBM1001 Specifications Max. lifting capacity 2.000kg Min. height 181mm Max. height 345mm Spindle travel 48mm Lifting height 116mm Features - Controlled release system - Compact design - Large lifting range - Storage case Includes	TROLLY JACK KIT MAX. 2000KG TJM1008 Specifications Max. lifting capacity 2.000kg Min. height 135mm Max. height 356mm Lifting height 221mm Features - Solid construction with integrated safety valve against overloading - Control release system - Two ball bearing castors - Carrying handle - Storage case Includes
ARC WELDER 40 - 100A WEM1042 Specifications Mains voltage 230V~, 50Hz Welding current 40-100A Electrode thickness 1.6-2.5mm Welding cable 2.1m Earth cable 1.5m Features - Current indicator - Thermal cut-out with control lamp - Forced cooling Includes Welding mask - Scaling hammer/ Steel-wire brush - Quick instruction card Optional Accessories Electrodes 12pcs WEA1016 (2mm) - WEA1017 (2.6mm) - Electrodes 1kg WEA1011 (2mm) - WEA1012 (2.6mm) - Electrodes 5kg WEA1014 (2.6mm)	ARC WELDER 55 - 160A WEM1035 Specifications Mains voltage 230/400V~, 50Hz Welding current 400V max. 160A 230V max. 140A Electrode thickness 2.0-4.0mm Welding cable 2.1m Earth cable 1.5m Features - Current indicator - Thermal cut-out with control lamp - Suitable for use with either 230V~ or 400V~ - Forced cooling Includes Welding mask - Scaling hammer/ Steel-wire brush - Quick instruction card Optional Accessories Electrodes 12pcs WEA1016 (2mm) - WEA1017 (2.6mm) - WEA1018 (3.2mm) - Electrodes 1kg WEA1011 (2mm) - WEA1012 (2.6mm) - WEA1013 (3.2mm) - Electrodes 5kg WEA1014 (2.6mm) - WEA1015 (3.2mm)	ELECTRIC LEVER HOIST 500W LHM1011 Specifications Mains voltage 230V~, 50Hz Power input 500W Rated load with pulley 250 kg Rated load without pulley 125 kg Lifting height with pulley 6m Lifting height without pulley 12m Lifting speed with pulley 4m/min. Lifting height without pulley 8m/min. Features - High lifting capacity - Long lifting cable - Non rotating steel rope - Remote control equipped with safety switch Includes Mounting brackets - Load hooks	PLATFORM TRUCK MAX. 150KG TTM1027 Specifications Max. carrying capacity 150kg Platform dimensions 734x480mm 2 Swivel wheels 2 Fixed wheels Features - Rubber wheels - Foldable push bar - Large plateau Includes

HAND TRUCK MAX. 225KG TTM1028 Specifications Max. carrying capacity225kg Size1.130x545x430mm Lifting plate thickness3.5mm  Features - Ball bearing wheels with inflatable tyres - Stable base plate - Steel rims	PORTABLE COMPRESSOR 1100W CRM1049 Specifications Mains voltage230V~, 50Hz Power input1.100W (S3-15%) No load speed3.550/min. Air displacement180 liter/min.  Features - Oil free - 3m Rubber hose with universal quick coupling - Carrying handle with soft grip - 5m cable IncludesTyre inflator with manometer - Blow gun nozzle - 3 Adapters	PAINT SPRAY GUN ATM1039 Specifications Operating pressure4.5-6 bar Container capacity400 cc  IncludesDIN coupling - Orion coupling	TYRE INFLATOR ATM1041 Specifications Operating pressure0-8 bar  IncludesDIN coupling - Orion coupling
OIL LUBRICATED COMPRESSOR 1.1HP - 750W - 8L CRM1044 Specifications Mains voltage230V~, 50Hz Power input750W-1.1HP Tank capacity8L No load speed2.850/min. Air displacement118 liter/min.  Features - Powerful single cylinder pump - Pressure adjustment from 0-8 bar - Silent direct drive induction motor - Universal ¼" quick coupling - 2 Manometers for tank and outlet pressure IncludesOil Optional AccessoriesAir accessory set 6pcs ATA1025 Coiled hose 5m + couplings ATA1026 Air hose 10m + coupling ATA1027 Hose reel 9m ATA1033	OIL LUBRICATED COMPRESSOR 1.5HP - 1100W - 24L CRM1045 Specifications Mains voltage230V~, 50Hz Power input1100W-1.5HP Tank capacity24L No load speed2.850/min. Air displacement155 liter/min.  Features - Powerful single cylinder pump - Pressure adjustment from 0-8 bar - Silent direct drive induction motor - Universal ¼" quick coupling - 2 Manometers for tank and outlet pressure IncludesOil Optional AccessoriesAir accessory set 6pcs ATA1025 Coiled hose 5m + couplings ATA1026 Air hose 10m + coupling ATA1027 Hose reel 9m ATA1033	AIR TOOL SET, 5PCS ATM1036 Specifications Spray gun - Operating pressure 4.5-6 bar - Container capacity 400 cc Tyre inflator with pressure gauge - Operating pressure 0-8 bar Air blow gun - Recommended pressure 2-4 bar Cleaning gun - Recommended pressure 2-4 bar 5m Coiled hose - Connection universal / DIN 	PNEUMATIC TACKER ATM1042 Specifications Operating pressure4-7 bar Staple length12-25mm gauge 18 Staple width5.8mm Staple capacity100 pcs  IncludesOil - 100 Staples 25mm - DIN coupling - Orion coupling - Storage case - 2 hex keys Optional AccessoriesStaples ATA1028 (1800pcs - 12mm) - ATA1029 (1300pcs - 18mm) - ATA1030 (1100pcs - 22mm) - ATA1031 (1000pcs - 25mm)
OIL LUBRICATED COMPRESSOR 2HP - 1500W - 50L CRM1046 Specifications Mains voltage230V~, 50Hz Power input1.500W-2HP Tank capacity50L No load speed2.850/min. Air displacement206 liter/min.  Features - Powerful single cylinder pump - Pressure adjustment from 0-8 bar - Silent direct drive induction motor - Universal ¼" quick coupling - 2 Manometers for tank and outlet pressure IncludesOil Optional AccessoriesAir accessory set 6pcs ATA1025 Coiled hose 5m + couplings ATA1026 Air hose 10m + coupling ATA1027 Hose reel 9m ATA1033	COMPRESSOR HOSE REEL ATA1033 Specifications Outlet9m hose Operating pressure8 bar  IncludesDIN coupling - Orion coupling	AIR NAILER/STAPLER ATM1051 Specifications Operating pressure4-7 bar Staple length16-40mm gauge 18 Staple width5.7mm Nail length15-50mm gauge 18 Staple capacity100 pcs  IncludesOil - 100 staples 40mm - 100 nails 20mm - 100 nails 30mm - 100 nails 50mm - 2 hex keys - DIN coupling - Orion coupling - Storage case Optional AccessoriesStaples ATA1029 (1300pcs - 18mm) - ATA1030 (1100pcs - 22mm) - ATA1031 (1000pcs - 25mm) Nails ATA1086 (1000pcs - 20mm) - ATA1087 (1000pcs - 30mm) - ATA1088 (1000pcs - 50mm)	IMPACT WRENCH ATM1043 Specifications Operating pressure6.3 bar No load speed7.000/min Bolt size capacity16mm Max. torque310Nm Drive shaft½" square  Includes10 Air sockets - 5" Extension bar - Oil - HEX wrench - Nipple - Mini oiler - DIN coupling - Orion coupling - Storage case





ACCESSORIES

DIAMOND DISC 115MM OPEN AGA1018 For AGM1086 and AGM1060S	STAPLES 18MM 1.300 PCS ATA1029 For ATM1042 and ATM1051
DIAMOND DISC 125MM OPEN AGA1019 For AGM1087 and AGM1061S	STAPLES 22MM 1.100 PCS ATA1030 For ATM1042 and ATM1051
DIAMOND DISC 115MM CLOSED AGA1020 For AGM1086 and AGM1060S	STAPLES 25MM 1.000 PCS ATA1031 For ATM1042 and ATM1051
DIAMOND DISC 125MM CLOSED AGA1021 For AGM1087 and AGM1061S	STAPLES 30MM 1.000 PCS ATA1048 For ATM1051
AIR ACCESSORY SET 6 PCS ATA1025 For CRM1044, CRM1045 and CRM1046	STAPLES 40MM 1.000 PCS ATA1049 For ATM1051
	STEEL NAILS 20MM 1.000 PCS ATA1086 For ATM1044 and ATM1051
COILED HOSE 5M + COUPLINGS ATA1026 For CRM1044, CRM1045 and CRM1046	STEEL NAILS 30MM 1.000 PCS ATA1087 For ATM1044 and ATM1051
	STEEL NAILS 50MM 1.000 PCS ATA1088 For ATM1044 and ATM1051
AIR HOSE 10M + COUPLINGS ATA1027 For CRM1044, CRM1045 and CRM1046	GRINDING STONE 150X16X12, 7MM P36 GREY BGA1053 For BGM1019
	GRINDING STONE 150X16X12, 7MM P60 GREY BGA1054 For BGM1019
STAPLES 12MM 1.800 PCS ATA1028 For ATM1042	GRINDING STONE 150X20X12, 7MM P36 GREY BGA1055 For BGM1020 and BGM1021


ACCESSORIES

GRINDING STONE 150X40X12, 7MM P80 WHITE BGA1056 For BGM1020	SANDING BELT SET P60 P100, P120, 3 PCS 533X75MM BSA1013 For BSM1024
GRINDING STONE 200X40X20MM, WET USE BGA1057 For BGM1021	BISCUITS 56X23X4MM 50 PCS BJA1004 For BJM1009
SANDING DISC SET 2X P80 3X P120 180MM AGA1022 For AGM1084P and AGM1037	SAW BLADE BJA1005 For BJM1009
POLISH SET 5 PCS 180MM AGA1023 For AGM1084P and AGM1037	BATTERY 12V - 1.5AH LI-ION CDA1085 For CDM1118 and CDM1119
SANDING DISC SET 2X P60 5X P100, 3X P150 150MM BGA1036 For BGM1003	BATTERY 18V - 1.5AH LI-ION CDA1087 For CDM1120 and CDM1131
SANDING DISC SET P100, 10 PCS 150MM BGA1037 For BGM1003	BATTERY 12V - 1.5AH LI-ION CDA1094 For JSM1026, OTM1006, CTM1016
SANDING DISC SET P150, 10 PCS 150MM BGA1038 For BGM1003	BATTERY 18V - 4.0AH LI-ION CDA1096 For CDM1127
SANDING DISC SET P60 P100 P150, 10 PCS 150MM BGA1039 For BGM1003	GUIDE RAIL SET CSA1049 For CSM1043
SANDING DISC SET 2X P60 5X P100, 3X P150 150MM BGA1062 For BGM1022	
SANDING BELT SET P60 P100 P150, 3 PCS 915X100MM BGA1058 For BGM1003 and BGM1062	COMBITOOL SET 100 PCS CTA1007 For CTM1016, CTM1010 and CTM1012
SANDING BELT SET P100, 3 PCS 915X100MM BGA1060 For BGM1003 and BGM1062	






ACCESSORIES

COMBITOOL SET 40 PCS CTA1008 <i>For CTM1016, CTM1010 and CTM1012</i>		PRECISION SAW BLADE 85X15 DIAMOND CSA1046 <i>For CSM1043</i>		
		PRECISION SAW BLADE 85X15 24T (TCT) CSA1047 <i>For CSM1043</i>		
SAW BLADE 185MM 24T CSA1007 <i>For CSM1039</i>		PRECISION SAW BLADE 85X15 44T (HSS) CSA1048 <i>For CSM1043</i>		
SAW BLADE 200X30/16 24T MSA1021 <i>For TSM1032</i>		SANDING BELT SET 10MM 8 PCS, 2XP40, 3XP80, 3XP120 EFA1003 <i>For EFM1001</i>		
SAW BLADE 200X30/16 40T MSA1022 <i>For TSM1032</i>		SANDING BELT SET 13MM 8 PCS, 2XP40, 3XP80, 3XP120 EFA1004 <i>For EFM1001</i>		
SAW BLADE 210X30/16/18 24T MSA1024 <i>For MSM1035, MSM1037 and TSM1035</i>		NAILS 15MM 1500 PCS I-SHAPE ETA1005 <i>For ETM1004</i>		
SAW BLADE 210X30/16/18 40T MSA1025 <i>For MSM1035, MSM1037 and TSM1035</i>		STAPLES 8MM 2000 PCS U-SHAPE ETA1009 <i>For ETM1004, ETM1005</i>		
SAW BLADE 250X30/16 40T MSA1026 <i>For TSM1033</i>		STAPLES 10MM 2000 PCS U-SHAPE ETA1013 <i>For ETM1004, ETM1005</i>		
SAW BLADE 250X30/16 72T MSA1027 <i>For TSM1033</i>		STAPLES 12MM 2000 PCS U-SHAPE ETA1014 <i>For ETM1004, ETM1005</i>		
SAW BLADE 255X30/16 40T MSA1028 <i>For MSM1038</i>		STAPLES 14MM 2000 PCS U-SHAPE ETA1010 <i>For ETM1004</i>		
SAW BLADE 255X30/16 72T MSA1029 <i>For MSM1038</i>		GLUE STICKS 11.2X100MM 6 PCS GGA1002 <i>For GGM1002</i>		

ACCESSORIES

GLUE STICKS 7X150MM 6 PCS GGA1003 <i>For GGM1003</i>		WHISK 120X680MM PMA1004 <i>For PMM1006</i>		
GLUE STICKS 11.2X150MM 12 PCS GGA1005 <i>For GGM1004</i>				
BRUSH GRA1001 <i>For GRM1022</i>		ROUTER BITS SET 20 PCS PRA1008 <i>For PRM1015 and PRM1021</i>		
ROTARY BRUSH GRA1002 <i>For GRM1022</i>				
JIG SAW BLADES 10 PCS JSA1004 <i>For JSM1014, JSM1023 and JSM1026</i>		SANDING PAPER SET P80 5 PCS PSA1007 <i>For PSM1013</i>		
PLUNGE CUTTING BLADE OTA1001 <i>For OTM1005 and OTM1006</i>				
SCRAPING KNIFE OTA1002 <i>For OTM1005 and OTM1006</i>		SANDING PAPER SET P120 5 PCS PSA1008 <i>For PSM1013</i>		
SANDING PAD OTA1003 <i>For OTM1005 and OTM1006</i>				
HSS SEGMENT SAW BLADE OTA1004 <i>For OTM1005 and OTM1006</i>		SANDING PAPER SET P60, P80 P120, 5 PCS PSA1031 <i>For PSM1024</i>		
CARBIDE BLADE OTA1005 <i>For OTM1005 and OTM1006</i>				
CHISEL SET 82MM 2 PCS PPA1003 <i>For PPM1010</i>		SANDING PAPER SET P80 10 PCS PSA1033 <i>For DSM1009 and OTM1005</i>		
				
		SANDING PAPER SET P120 10 PCS PSA1034 <i>For DSM1009 and OTM1005</i>		
				
		SAW BLADES RECIPROCATING SAW 9 PCS RSA1001 <i>For RSM1019</i>		
				
		SCROLL SAW BLADE 15TPI 5 PCS SSA1001 <i>For SSM1005</i>		
				

ACCESSORIES

SCROLL SAW BLADE 10TPI 5 PCS SSA1002 For SSM1005 	ELECTRODES 2.6MM 12 PCS WEA1017 For WEM1035 and WEM1042 
SCROLL SAW BLADE 18TPI 5 PCS SSA1003 For SSM1005 	ELECTRODES 3.2MM 12 PCS WEA1018 For WEM1035 and WEM1042 
SCROLL SAW BLADE 25TPI 5 PCS SSA1004 For SSM1005 	WELDING HELMET WEA1058 
DIAMOND SAW BLADE 180MM TCA1004 For TCM1010 	
DIAMOND SAW BLADE 200MM TCA1006 For TCM1011 	SAW BLADE SET 125MM, 2 PCS DIAMOND WSA1001 For WSM1009 
ELECTRODES 2.0MM 1 KG WEA1011 For WEM1035 and WEM1042 	SAW BLADE SET 150MM, 2 PCS DIAMOND WSA1002 For WSM1008 
ELECTRODES 2.6MM 1 KG WEA1012 For WEM1035 and WEM1042 	MACHINE VICE TDA1013 For TDM1025 and TDM1026 
ELECTRODES 3.2MM 1 KG WEA1013 For WEM1035 	
ELECTRODES 2.6MM 5 KG WEA1014 For WEM1035 and WEM1042 	
ELECTRODES 3.2MM 5 KG WEA1015 For WEM1035 	
ELECTRODES 2.0MM 12 PCS WEA1016 For WEM1035 and WEM1042 	

WWW.FERM.COM

1808-03