

FERM[®]

INDUSTRIAL



DEVELOPED IN THE NETHERLANDS

CATALOG

FERM INDUSTRIAL

AFFORDABLE INDUSTRIAL POWER TOOLS

Since the company began in 1965 in Zwolle, The Netherlands, FERM grew to be one of the leading power tool brands in Europe. FERM strives to ensure 100% confidence and satisfaction to its customers worldwide, by offering durable and high-performance Industrial power tools, for an affordable price.

With a renewed focus, FERM invested time to work side-by-side with real users of professional tools to understand their specific demands at the jobsite. Especially for craftsmen, construction workers, tradesmen and other professionals who require professional power tools for an affordable price, FERM designed, developed and produced its FERM INDUSTRIAL power tool assortment.

FERM INDUSTRIAL power tools consists of a wide range of affordable high quality power tools and accessories for the professional market. FERM also offers competitively priced spare parts and excellent serviceability of our power tools. All FERM Industrial products are developed, produced and tested according to the strict European standards and our company is known for its quality products and excellent service.

Rick Rosberg
CEO



ANGLE GRINDER 710W - 100MM AGM1110P Specifications Mains voltage220-240V~, 50/60Hz Power input710W Disc diameter100mm No load speed11.000/min. SpindleM10 Machine weight1.98kg Features - Electronic restart protection - Lock-on switch - Spindle lock - Adjustable open safety guard - 3m rubber cable Includes Side handle - Wrench Availability FOB 	ANGLE GRINDER 750W - 100MM AGM1093P Specifications Mains voltage220-240V~, 50Hz Power input750W Disc diameter100mm No load speed11.000/min. SpindleM10 Machine weight1.90kg Features - Electronic restart protection - Lock-on switch - Spindle lock - Adjustable open safety guard - 3m rubber cable Includes Side handle - Wrench Availability FOB 
ANGLE GRINDER 850W - 100MM AGM1111P Specifications Mains voltage220-240V~, 50/60Hz Power input850W Disc diameter100mm No load speed11.000/min. SpindleM10 Machine weight1.98kg Features - Electronic restart protection - Lock-on switch - Spindle lock - Adjustable open safety guard - 3m rubber cable Includes Side handle - Wrench Availability FOB 	ANGLE GRINDER 710W - 115MM AGM1112P Specifications Mains voltage220-240V~, 50/60Hz Power input710W Disc diameter115mm No load speed11.000/min. SpindleM14 Machine weight2.00kg Features - Electronic restart protection - Lock-on switch - Spindle lock - Adjustable open safety guard - 3m rubber cable Includes Side handle - Wrench Availability Exworks + FOB 
ANGLE GRINDER 750W - 115MM AGM1094P Specifications Mains voltage220-240V~, 50Hz Power input750W Disc diameter115mm No load speed11.000/min. SpindleM14 Machine weight2.00kg Features - Electronic restart protection - Lock-on switch - Spindle lock - Adjustable open safety guard - 3m rubber cable Includes Side handle - Wrench Availability Exworks + FOB 	ANGLE GRINDER 850W - 115MM AGM1113P Specifications Mains voltage220-240V~, 50/60Hz Power input850W Disc diameter115mm No load speed11.000/min. SpindleM14 Machine weight2.00kg Features - Electronic restart protection - Lock-on switch - Spindle lock - Adjustable open safety guard - 3m rubber cable Includes Side handle - Wrench Availability FOB 
ANGLE GRINDER 950W - 115MM AGM1103P Specifications Mains voltage230-240V~, 50Hz Power input950W Disc diameter115mm No load speed12.000/min. SpindleM14 Machine weight2.00kg Features - Electronic restart protection - Lock-on switch - Spindle lock - Adjustable open safety guard - 3m rubber cable Includes Side handle - Wrench Availability FOB 	ANGLE GRINDER 710W - 125MM AGM1114P Specifications Mains voltage220-240V~, 50/60Hz Power input710W Disc diameter125mm No load speed11.000/min. SpindleM14 Machine weight2.05kg Features - Electronic restart protection - Lock-on switch - Spindle lock - Adjustable open safety guard - 3m rubber cable Includes Side handle - Wrench Availability FOB 
ANGLE GRINDER 850W - 125MM AGM1115P Specifications Mains voltage220-240V~, 50/60Hz Power input850W Disc diameter125mm No load speed11.000/min. SpindleM14 Machine weight2.05kg Features - Electronic restart protection - Lock-on switch - Spindle lock - Adjustable open safety guard - 3m rubber cable Includes Side handle - Wrench Availability Exworks + FOB 	ANGLE GRINDER 950W - 125MM AGM1095P Specifications Mains voltage230-240V~, 50Hz Power input950W Disc diameter125mm No load speed12.000/min. SpindleM14 Machine weight2.10kg Features - Electronic restart protection - Lock-on switch - Spindle lock - Adjustable open safety guard - 3m rubber cable Includes Side handle - Wrench Availability Exworks + FOB 
ANGLE GRINDER 1400W - 125MM AGM1096P Specifications Mains voltage230V~, 50Hz Power input1.400W Disc diameter125mm No load speed12.000/min. SpindleM14 Machine weight3.90kg Features - Lock-off safety switch - Spindle lock - Adjustable open safety guard - 3m rubber cable Includes Side handle - Wrench Availability FOB 	ANGLE GRINDER 2300W - 180MM AGM1116P Specifications Mains voltage220-240V~, 50/60Hz Power input2.300W Disc diameter180mm No load speed8.500/min. SpindleM14 Machine weight6.00kg Features - Lock-off safety switch - Soft start - Spindle lock - Adjustable rear handle - Adjustable open safety guard - 3m rubber cable Includes Side handle - Wrench - Hex key Availability FOB 

ANGLE GRINDER 2600W - 180MM AGM1117P Specifications Mains voltage220-240V~, 50/60Hz Power input2.600W Disc diameter180mm No load speed8.500/min. SpindleM14 Machine weight6.60kg Features - Lock-off safety switch - Soft start - Spindle lock - Adjustable open safety guard - 3m rubber cable Includes Side handle - Wrench - Hex key Availability FOB 	ANGLE GRINDER 2300W - 230MM AGM1118P Specifications Mains voltage220-240V~, 50/60Hz Power input2.300W Disc diameter230mm No load speed6.500/min. SpindleM14 Machine weight6.10kg Features - Lock-off safety switch - Soft start - Spindle lock - Adjustable rear handle - Adjustable open safety guard - 3m rubber cable Includes Side handle - Wrench - Hex key Availability FOB 	
ANGLE GRINDER 2600W - 230MM AGM1119P Specifications Mains voltage220-240V~, 50/60Hz Power input2.600W Disc diameter230mm No load speed6.500/min. SpindleM14 Machine weight6.70kg Features - Lock-off safety switch - Soft start - Spindle lock - Adjustable open safety guard - 3m rubber cable Includes Side handle - Wrench - Hex key Availability Exworks + FOB 	CHOP SAW 2300W - 355MM COM1007P Specifications Mains voltage220-240V~, 50Hz Power input2.300W Disc diameter355mm No load speed4.000/min. SpindleØ1 inch / 25.4mm Machine weight15.80kg Features - Heavy duty base - Spindle lock - Quick lock vise - Adjustable depth stop - High cutting capacity - 4m rubber cable Includes Wrench - Cutting blade Optional accessories COA1005 Cutting disc 355x2.8x25.4mm Inox/ stainless steel Availability Exworks + FOB 	
CORDLESS LI-ION DRILL 20V CDM1144P FI20V Specifications Voltage20V No load speed position I0-450/min. No load speed position II0-1.700/min. Chuck capacityØ1.5-13mm Torque positions21+1 Max. torque (hard)50Nm Machine weight1.24kg (without battery pack) Features - 4-pole Mabuchi® motor - Metal Jacobs® chuck - Variable electronic speed control - LED light - Storage case Includes 2 screwdriver bits Optional accessories Battery CDA1132P, CDA1133P, CDA1148P Optional accessories Charger CDA1131P, CDA1147P Availability FOB 	CORDLESS LI-ION DRILL 20V - 2.0AH CDM1141P FI20V Specifications Charger voltage230-240V~, 50Hz Voltage20V Li-Ion (2.0Ah) No load speed position I0-450/min. No load speed position II0-1.700/min. Chuck capacityØ1.5-13mm Torque positions21+1 Max. torque (hard)50Nm Machine weight1.24kg (without battery pack) Features - 4-pole Mabuchi® motor - Metal Jacobs® chuck - Samsung® 2.0 Ah battery cells - 60 min. quick charger - Variable electronic speed control - LED light - Storage case Includes 2 Li-Ion 2.0 Ah batteries - 2 screwdriver bits - quick charger Optional accessories Battery CDA1132P, CDA1133P, CDA1148P Optional accessories Charger CDA1131P, CDA1147P Availability Exworks + FOB 	
BATTERY 20V - 2.0AH CDA1132P FI20V Specifications Voltage20V Ampere hour2.0Ah Battery typeLi-Ion Charging time45 min. (With CDA1147P) Charging time60 min. (With CDA1131P) Battery weight0.38 kg Features - Samsung® battery cells - Battery charge indication - Softgrip Availability FOB 	BATTERY 20V - 4.0AH CDA1133P FI20V Specifications Voltage20V Ampere hour4.0Ah Battery typeLi-Ion Charging time60 min. (With CDA1147P) Charging time90 min. (With CDA1131P) Battery weight0.65 kg Features - Samsung® battery cells - Battery charge indication - Softgrip Availability FOB 	BATTERY 20V - 6.0AH CDA1148P FI20V Specifications Voltage20V Ampere hour6.0Ah Battery typeLi-Ion Charging time90 min. (With CDA1147P) Battery weight0.92 kg Features - Samsung® battery cells - Battery charge indication - Softgrip Availability FOB 



QUICK CHARGER 20V - 2.0A CDA1131P Specifications Charger input100-240V 50/60Hz, 50W Charger output20V 2A Charger weight0.36 kg  Features - Charge indication - Charging time with CDA1132P 60 minutes - Charging time with CDA1133P 90 minutes Optional Accessories Battery CDA1132P, CDA1133P Availability FOB	QUICK CHARGER 20V - 4.0A CDA1147P Specifications Charger input100-240V 50/60Hz, 98W Charger output20V 4A Charger weight0.53 kg  Features - Charge indication - Charging time with CDA1132P 45 minutes - Charging time with CDA1133P 60 minutes - Charging time with CDA1148P 90 minutes Optional Accessories Battery CDA1132P, CDA1133P, CDA1148P Availability FOB	IMPACT DRILL 710W - 13MM PDM1049P Specifications Mains voltage220-240V~, 50Hz Power input710W No load speed0-3.200/min. Impact rate0-51.200/min. Chuck capacityØ1.5-13mm Machine weight2.00kg  Features - Double function (drilling and impact drilling) - Variable electronic speed control - Side handle with metal depth limiter - 3m rubber cable Includes Chuck key - Auxiliary handle - Metal depth limiter Availability Exworks + FOB	IMPACT DRILL 710W - 13MM PDM1049P_K Specifications Mains voltage220-240V~, 50Hz Power input710W No load speed0-3.200/min. Impact rate0-51.200/min. Chuck capacityØ1.5-13mm Machine weight2.00kg  Features - Keyless metal chuck - Double function (drilling and impact drilling) - Variable electronic speed control - Side handle with metal depth limiter - 3m rubber cable Includes Auxiliary handle - Metal depth limiter Availability Exworks + FOB
ELECTRIC DRILL 230W - 6.5MM PDM1047P Specifications Mains voltage220-240V~, 50Hz Power input230W No load speed0-4.500/min. Chuck capacityØ0.5- 6.5mm Machine weight1.20kg  Features - Single function (drilling) - Compact design - Left/right rotation - Variable electronic speed control - 3m rubber cable Includes Chuck key Availability FOB	ELECTRIC DRILL 450W - 10MM PDM1048P Specifications Mains voltage220-240V~, 50Hz Power input450W No load speed0-3.300/min. Chuck capacityØ1.5-10mm Machine weight1.50kg  Features - Single function (drilling) - Left/right rotation - Variable electronic speed control - 3m rubber cable Includes Chuck key Availability Exworks + FOB	IMPACT DRILL 850W - 13MM PDM1060P Specifications Mains voltage220-240V~, 50/60Hz Power input850W No load speed0-3.000/min. Impact rate0-48.000/min. Chuck capacityØ1.5-13mm Machine weight2.08kg  Features - Double function (drilling and impact drilling) - Variable electronic speed control - Side handle with metal depth limiter - 3m rubber cable - Storage case Includes Chuck key - Auxiliary handle - Metal depth limiter Availability FOB	IMPACT DRILL 850W - 13MM PDM1060P_K Specifications Mains voltage220-240V~, 50/60Hz Power input850W No load speed0-3.000/min. Impact rate0-48.000/min. Chuck capacityØ1.5-13mm Machine weight2.08kg  Features - Keyless metal chuck - Double function (drilling and impact drilling) - Variable electronic speed control - Side handle with metal depth limiter - 3m rubber cable - Storage case Includes Auxiliary handle - Metal depth limiter Availability Exworks + FOB
ELECTRIC DRILL 650W - 13MM PDM1059P Specifications Mains voltage220-240V~, 50-60Hz Power input650W No load speed0-3.000/min. Chuck capacityØ1.5-13mm Machine weight1.82kg  Features - Left/right rotation - Single function (drilling) - Variable electronic speed control - 3m rubber cable Includes Chuck key Availability FOB	ELECTRIC DRILL 650W - 13MM PDM1059P_K Specifications Mains voltage220-240V~, 50-60Hz Power input650W No load speed0-3.000/min. Chuck capacityØ1.5-13mm Machine weight1.82kg  Features - Keyless metal chuck - Left/right rotation - Single function (drilling) - Variable electronic speed control - 3m rubber cable Availability FOB	IMPACT DRILL 1100W - 13MM PDM1061P Specifications Mains voltage220-240V~, 50/60Hz Power input1.100W Mechanical speeds2 No load speed0-1.200/min. 0-3.100/min. Impact rate0-19.200/min. 0-49.600/min. Chuck capacityØ1.5-13mm Machine weight3.28kg  Features - Double function (drilling and impact drilling) - Mechanical 2 speed gearbox - Metal gear housing - Variable electronic speed control - Side handle with metal depth limiter - 3m rubber cable - Storage case Includes Chuck key - Auxiliary handle - Metal depth limiter Availability FOB	IMPACT DRILL 1100W - 13MM PDM1061P_K Specifications Mains voltage220-240V~, 50/60Hz Power input1.100W Mechanical speeds2 No load speed0-1.200/min. 0-3.100/min. Impact rate0-19.200/min. 0-49.600/min. Chuck capacityØ1.5-13mm Machine weight3.28kg  Features - Keyless metal chuck - Double function (drilling and impact drilling) - Mechanical 2 speed gearbox - Metal gear housing - Variable electronic speed control - Side handle with metal depth limiter - 3m rubber cable - Storage case Includes Auxiliary handle - Metal depth limiter Availability Exworks + FOB

ROTARY HAMMER 800W - 3.3KG HDM1038P Specifications Mains voltage220-240V~, 50Hz Power input800W No load speed0-1.250/min. Impact rate0-5.500/min. Chuck sizeSDS-plus Impact energy2.7 Joule Machine weight3.30kg  Features - 4 Functions (drilling, hammer drilling, chiseling, free rotation chiseling) - Universal SDS-plus chuck - Variable electronic speed control - 3m rubber cable - Storage case IncludesAuxiliary handle - Metal depth limiter - 3 SDS concrete drills - Chisel pointed - Chisel flat AvailabilityExworks + FOB	ROTARY HAMMER 1100W - 6.6KG HDM1043P Specifications Mains voltage220-240V~, 50Hz Power input1.100W No load speed300-760/min. Impact rate1.950-4.860/min. Chuck sizeSDS-max Impact energy1-7 Joule Machine weight6.60kg Drilling capacity35mm  Features - 3 Functions (hammer drilling, chiseling, free rotation chiseling) - SDS-max chuck - Soft start - Variable electronic speed control - Vibration reduction rear handle - 5m rubber cable - Storage case IncludesAuxiliary handle - Depth limiter AvailabilityExworks + FOB	JIG SAW 750W JSM1025P Specifications Mains voltage230-240V~, 50Hz Power input750W No load speed500-3.000/min. Bevel adjustment0-45° Machine weight3.30kg  Features - Variable electronic speed control - Toolless saw blade release - 4 pendulum positions - Variable angle adjustment (0-45°) - 4m rubber cable - Storage case IncludesSaw blade wood - Splinter plate - Vacuum cleaner adapter - Anti-scratch plate - Parallel guide AvailabilityExworks + FOB	CIRCULAR SAW 2200W - 235MM CSM1042P Specifications Mains voltage220-240V~, 50Hz Power input2.200W No load speed3.900/min. Saw blade diameterØ235mm Saw blade boreØ30mm Bevel adjustment0-45° Machine weight7.00kg  Features - Angle and depth adjustment - Spindle lock - Lock-off safety switch - High quality blade included - 3m rubber cable IncludesSaw blade 235mm - Hexagon key - Parallel guide AvailabilityFOB
DEMOLITION HAMMER 1200W - 6.2KG HDM1040P Specifications Mains voltage220-240V~, 50Hz Power input1.200W Impact rate3.100/min. Chuck sizeSDS-max Impact energy14 Joule Machine weight6.20kg  Features - Single function (chiselling) - SDS-max chuck - Powerful lightweight machine (14 joule - 6.2kg) - 12 step adjustable chisel position - Vibration reduction rear handle - 5m rubber cable - Storage case IncludesAuxiliary handle - Chisel pointed - Chisel flat AvailabilityExworks + FOB	DEMOLITION HAMMER 1500W - 11KG HDM1049P Specifications Mains voltage220-240V~, 50Hz Power input1.500W Impact rate1.000-1.900/min. Chuck sizeSDS-max Impact energy6-25 Joule Machine weight11.00kg  Features - Single function (chiselling) - SDS-max chuck - Powerful heavy duty machine (6 - 25 joule - 11.0kg) - 12 step adjustable chisel position - Vibration reduction rear handle - 5m rubber cable - Storage case IncludesAuxiliary handle - Chisel pointed - Chisel flat AvailabilityExworks + FOB	ORBITAL SANDER 220W - 1/4 SHEET PSM1028P Specifications Mains voltage220-240V~, 50Hz Power input220W No load speed15.000/min. Sanding surface105x113mm Paper size140x114mm Machine weight1.40kg  Features - Aluminum Velcro® base plate - Paper clamping system - Active dust extraction - Soft grip - 4m rubber cable IncludesDust bag - Sanding sheet (Velcro®) - Perforation plate AvailabilityExworks + FOB	ORBITAL SANDER 350W - 1/3 SHEET PSM1029P Specifications Mains voltage220-240V~, 50Hz Power input350W No load speed13.000/min. Sanding surface93x185mm Paper size93x230mm Machine weight2.00kg  Features - Aluminum Velcro® base plate - Paper clamping system - Active dust extraction - Soft grip - 4m rubber cable IncludesDust bag - Sanding sheet (Velcro®) - Perforation plate AvailabilityExworks + FOB
DEMOLITION HAMMER 1500W - 16KG HDM1042P Specifications Mains voltage230V~, 50Hz Power input1.500W Impact rate1.400/min. Chuck sizeHex 30mm Impact energy50 Joule Machine weight16.00kg  Features - Single function (chiselling) - Hex 30mm chuck - Powerful heavy duty machine (50 joule - 16kg) - Vibration reduction rear handle - 5m rubber cable - Storage case (with transport wheels) IncludesAuxiliary handle - Chisel pointed - Chisel flat AvailabilityExworks + FOB	JIG SAW 450W JSM1028P Specifications Mains voltage220-240V~, 50Hz Power input450W No load speed0-3.400/min. Bevel adjustment0-45° Machine weight2.10kg  Features - Variable electronic speed control - 4 pendulum positions - Variable angle adjustment (0-45°) - 3m rubber cable - Storage case IncludesSaw blade wood - Saw blade steel AvailabilityExworks + FOB	ORBITAL SANDER 520W - 1/2 SHEET PSM1030P Specifications Mains voltage220-240V~, 50Hz Power input520W No load speed10.000/min. Sanding surface114x234mm Paper size114x278mm Machine weight2.70kg  Features - Aluminum base plate - Paper clamping system - Powerful motor - 4m rubber cable IncludesSanding sheet AvailabilityFOB	BELT SANDER 1200W - 100MM BSM1025P Specifications Mains voltage230V~, 50Hz Power input1.200W Belt speed500m/min. Belt size100x610mm Machine weight6.20kg  Features - Aluminum belt frame - Lock-on switch - Easy belt change - Belt tracking device - 3m rubber cable IncludesDust bag - Sanding belt AvailabilityFOB

Specifications

Mains voltage	220-240V~, 50Hz
Power input	2.200W
No load speed	9.000-22.000/min.
Collet size	Ø12mm
Machine weight	5.80kg



Includes	Router bit - Parallel guide - Roller guide - Template guide - Wrench - Collet Ø6mm - Collet Ø8mm - Collet Ø12mm
Availability	Exworks + FOB

Specifications	
Mains voltage	220-240V~, 50Hz
Power input	550W
No load speed	35.000/min.
Collet size	Ø6mm
Machine weight	1.60kg



Includes	Router bit - Parallel guide - Edge guide - Template guide - Wrench - Collet Ø6mm
Availability	FOB

Specifications	
Mains voltage	230V~, 50Hz
Power input	2.400W
Disc diameter	150mm
No load speed	8.000/min.
Spindle	22.2mm
Cutting depth	0-43mm
Cutting width	30mm
Machine weight	6.10kg



Includes	Spanners - 3-in-1 blade
Optional accessories	WCA1001 Wall chaser blade 3-in-1 (150x22.2mm)
Availability	Exworks + FOB

Specifications	
Mains voltage	220-240V~, 50/60Hz
Power input	1.400W
Disc diameter	125mm
No load speed	12.000 /min.
Disc bore	Ø20mm
Machine weight	3.20kg



Includes	Diamond disc - Hexagon key - Wrench - Water line set
Availability	FOB

Specifications	
Mains voltage	220-240V~, 50Hz
Power input	2.000W
Temperature setting	Variable
Temp/air volume setting 1:	50°C (250L/min.)
Temp/air volume setting 2:	50°-450°C (250L/min.)
Temp/air volume setting 3:	90°-600°C (500L/min.)
Machine weight	0.90kg



Availability Exworks + FOB

Specifications	
Mains voltage	220-240V~, 50Hz
Power input	1.400W
Disc diameter	180mm
No load speed	1.000-3.300/min.
Spindle	M14
Machine weight	3.10kg



Includes	Front handle - Hexagon key - Base plate (Velcro®) - Polishing foam pad - Polishing wool pad - Nylon accessory bag
Optional accessories	AGA1033P Polish set 180mm 2 pc.
Availability	Exworks + FOB



WWW.FERM-INDUSTRIAL.COM

2009-07