

# **FERM<sup>®</sup>**

## **INDUSTRIAL**



**DEVELOPED IN THE NETHERLANDS**

***CATALOG***

## ***FERM INDUSTRIAL***

### ***AFFORDABLE INDUSTRIAL POWER TOOLS***

Since the company began in 1965 in Zwolle, The Netherlands, FERM grew to be one of the leading power tool brands in Europe. FERM strives to ensure 100% confidence and satisfaction to its customers worldwide, by offering durable and high-performance Industrial power tools, for an affordable price.

With a renewed focus, FERM invested time to work side-by-side with real users of professional tools to understand their specific demands at the jobsite. Especially for craftsmen, construction workers, tradesmen and other professionals who require professional power tools for an affordable price, FERM designed, developed and produced its FERM INDUSTRIAL power tool assortment.

FERM INDUSTRIAL power tools consists of a wide range of affordable high quality power tools and accessories for the professional market. FERM also offers competitively priced spare parts and excellent serviceability of our power tools. All FERM Industrial products are developed, produced and tested according to the strict European standards and our company is known for its quality products and excellent service.

Rick Rosberg  
CEO



**ANGLE GRINDER**  
**710W - 100MM AGM1110P**

**Specifications**

Mains voltage	220-240V~, 50/60Hz
Power input	710W
Disc diameter	100mm
No load speed	11.000/min.
Spindle	M10
Machine weight	1.98kg

**Features**

- Electronic restart protection
- Lock-on switch
- Spindle lock
- Adjustable open safety guard
- 3m rubber cable



Includes Side handle - Wrench  
Availability Available on request

**ANGLE GRINDER**  
**750W - 100MM AGM1093P**

**Specifications**

Mains voltage	220-240V~, 50Hz
Power input	750W
Disc diameter	100mm
No load speed	11.000/min.
Spindle	M10
Machine weight	1.90kg

**Features**

- Electronic restart protection
- Lock-on switch
- Spindle lock
- Adjustable open safety guard
- 3m rubber cable



Includes Side handle - Wrench  
Availability Available on request

**ANGLE GRINDER**  
**950W - 115MM AGM1103P**

**Specifications**

Mains voltage	230-240V~, 50Hz
Power input	950W
Disc diameter	115mm
No load speed	12.000/min.
Spindle	M14
Machine weight	2.00kg

**Features**

- Electronic restart protection
- Lock-on switch
- Spindle lock
- Adjustable open safety guard
- 3m rubber cable



Includes Side handle - Wrench  
Availability Available on request

**ANGLE GRINDER**  
**710W - 125MM AGM1114P**

**Specifications**

Mains voltage	220-240V~, 50/60Hz
Power input	710W
Disc diameter	125mm
No load speed	11.000/min.
Spindle	M14
Machine weight	2.05kg

**Features**

- Electronic restart protection
- Lock-on switch
- Spindle lock
- Adjustable open safety guard
- 3m rubber cable



Includes Side handle - Wrench  
Availability Available on request

**ANGLE GRINDER**  
**850W - 100MM AGM1111P**

**Specifications**

Mains voltage	220-240V~, 50/60Hz
Power input	850W
Disc diameter	100mm
No load speed	11.000/min.
Spindle	M10
Machine weight	1.98kg

**Features**

- Electronic restart protection
- Lock-on switch
- Spindle lock
- Adjustable open safety guard
- 3m rubber cable



Includes Side handle - Wrench  
Availability Available on request

**ANGLE GRINDER**  
**710W - 115MM AGM1112P**

**Specifications**

Mains voltage	220-240V~, 50/60Hz
Power input	710W
Disc diameter	115mm
No load speed	11.000/min.
Spindle	M14
Machine weight	2.00kg

**Features**

- Electronic restart protection
- Lock-on switch
- Spindle lock
- Adjustable open safety guard
- 3m rubber cable



Includes Side handle - Wrench  
Availability Ex-works + FOB

**ANGLE GRINDER**  
**850W - 125MM AGM1115P**

**Specifications**

Mains voltage	220-240V~, 50/60Hz
Power input	850W
Disc diameter	125mm
No load speed	11.000/min.
Spindle	M14
Machine weight	2.05kg

**Features**

- Electronic restart protection
- Lock-on switch
- Spindle lock
- Adjustable open safety guard
- 3m rubber cable



Includes Side handle - Wrench  
Availability Ex-works + FOB

**ANGLE GRINDER**  
**950W - 125MM AGM1095P**

**Specifications**

Mains voltage	230-240V~, 50Hz
Power input	950W
Disc diameter	125mm
No load speed	12.000/min.
Spindle	M14
Machine weight	2.10kg

**Features**

- Electronic restart protection
- Lock-on switch
- Spindle lock
- Adjustable open safety guard
- 3m rubber cable



Includes Side handle - Wrench  
Availability Ex-works + FOB

**ANGLE GRINDER**  
**750W - 115MM AGM1094P**

**Specifications**

Mains voltage	220-240V~, 50Hz
Power input	750W
Disc diameter	115mm
No load speed	11.000/min.
Spindle	M14
Machine weight	2.00kg

**Features**

- Electronic restart protection
- Lock-on switch
- Spindle lock
- Adjustable open safety guard
- 3m rubber cable



Includes Side handle - Wrench  
Availability Ex-works + FOB

**ANGLE GRINDER**  
**850W - 115MM AGM1113P**

**Specifications**

Mains voltage	220-240V~, 50/60Hz
Power input	850W
Disc diameter	115mm
No load speed	11.000/min.
Spindle	M14
Machine weight	2.00kg

**Features**

- Electronic restart protection
- Lock-on switch
- Spindle lock
- Adjustable open safety guard
- 3m rubber cable



Includes Side handle - Wrench  
Availability Available on request

**ANGLE GRINDER**  
**1400W - 125MM AGM1096P**

**Specifications**

Mains voltage	230V~, 50Hz
Power input	1.400W
Disc diameter	125mm
No load speed	12.000/min.
Spindle	M14
Machine weight	3.90kg

**Features**

- Lock-off safety switch
- Spindle lock
- Adjustable open safety guard
- 3m rubber cable



Includes Side handle - Wrench  
Availability Available on request

**ANGLE GRINDER**  
**2300W - 180MM AGM1116P**

**Specifications**

Mains voltage	220-240V~, 50/60Hz
Power input	2.300W
Disc diameter	180mm
No load speed	8.500/min.
Spindle	M14
Machine weight	6.00kg

**Features**

- Lock-off safety switch
- Soft start
- Spindle lock
- Adjustable rear handle
- Adjustable open safety guard
- 3m rubber cable



Includes Side handle - Wrench - Hex key  
Availability Available on request

**ANGLE GRINDER**  
**2600W - 180MM AGM1117P**

**Specifications**

Mains voltage	220-240V~, 50/60Hz
Power input	2.600W
Disc diameter	180mm
No load speed	8.500/min.
Spindle	M14
Machine weight	6.60kg

- Features**
- Lock-off safety switch
  - Soft start
  - Spindle lock
  - Adjustable open safety guard
  - 3m rubber cable



Includes Side handle - Wrench - Hex key  
Availability Available on request

**ANGLE GRINDER**  
**2300W - 230MM AGM1118P**

**Specifications**

Mains voltage	220-240V~, 50/60Hz
Power input	2.300W
Disc diameter	230mm
No load speed	6.500/min.
Spindle	M14
Machine weight	6.10kg

- Features**
- Lock-off safety switch
  - Soft start
  - Spindle lock
  - Adjustable rear handle
  - Adjustable open safety guard
  - 3m rubber cable



Includes Side handle - Wrench - Hex key  
Availability Available on request

**ANGLE GRINDER**  
**2600W - 230MM AGM1119P**

**Specifications**

Mains voltage	220-240V~, 50/60Hz
Power input	2.600W
Disc diameter	230mm
No load speed	6.500/min.
Spindle	M14
Machine weight	6.70kg

- Features**
- Lock-off safety switch
  - Soft start
  - Spindle lock
  - Adjustable open safety guard
  - 3m rubber cable



Includes Side handle - Wrench - Hex key  
Availability Ex-works + FOB

**CHOP SAW**  
**2300W - 355MM COM1007P**

**Specifications**

Mains voltage	220-240V~, 50Hz
Power input	2.300W
Disc diameter	355mm
No load speed	4.000/min.
Spindle	Ø1 inch / 25.4mm
Machine weight	15.80kg

- Features**
- Heavy duty base
  - Spindle lock
  - Quick lock vise
  - Adjustable depth stop
  - High cutting capacity
  - 4m rubber cable



Includes Wrench - Cutting blade  
Optional Accessories COA1005 Cutting disc 355x2.8x25.4mm Inox/ stainless steel  
Availability Ex-works + FOB

**CORDLESS LI-ION COMBI DRILL**  
**20V - 2.0AH CDM1152P**

**FI20V**

**Specifications**

Voltage	20V Li-Ion (2.0Ah)
No load speed position I	0-450/min.
No load speed position II	0-1.700/min.
No load impact rate position I	0-7.200/min.
No load impact rate position II	0-27.200/min.
Chuck capacity	Ø1.5-13mm
Torque positions	21
Max. torque (hard)	50Nm
Machine weight	1.26kg (without battery pack)

- Features**
- 4-pole Mabuchi® motor
  - Metal Jacobs® chuck
  - Variable electronic speed control
  - LED light
  - Storage case



Includes 2 Screwdriver bits  
Optional Accessories Battery CDA1132P, CDA1133P, CDA1148P  
Optional Accessories Charger CDA1131P, CDA1147P  
Availability Available on request

**CORDLESS LI-ION COMBI DRILL**  
**20V - 2.0AH CDM1147P**

**FI20V**

**Specifications**

Charger voltage	100-240V~, 50-60Hz, 50W
Voltage	20V Li-Ion (2.0Ah)
No load speed position I	0-450/min.
No load speed position II	0-1.700/min.
No load impact rate position I	0-7.200/min.
No load impact rate position II	0-27.200/min.
Chuck capacity	Ø1.5-13mm
Torque positions	21
Max. torque (hard)	50Nm
Machine weight	1.26kg (without battery pack)

- Features**
- 4-pole Mabuchi® motor
  - Metal Jacobs® chuck
  - High-quality 2.0 Ah battery cells
  - 60 min. quick charger
  - Variable electronic speed control
  - LED light
  - Storage case



Includes 2 Li-Ion 2.0 Ah batteries - 2 Screwdriver bits - Quick charger  
Optional Accessories Battery CDA1132P, CDA1133P, CDA1148P  
Optional Accessories Charger CDA1131P, CDA1147P  
Availability Ex-works + FOB

**CORDLESS LI-ION IMPACT DRIVER**  
**20V CDM1145P**

**FI20V**

**Specifications**

Voltage	20V
No load speed	0-2.900/min.
Impact rate	0-3.300/min.
Chuck type	1/4" (6.35mm) Hex
Max. torque	150Nm
Machine weight	1.16 kg (without battery pack)

- Features**
- 4-pole Mabuchi® motor
  - Quick-change hex chuck
  - Variable electronic speed control
  - LED light
  - Storage case



Includes 2 Screwdriver bits  
Optional Accessories Battery CDA1132P, CDA1133P, CDA1148P  
Optional Accessories Charger CDA1131P, CDA1147P  
Availability Available on request

**CORDLESS LI-ION IMPACT DRIVER**  
**20V - 2.0AH CDM1142P**

**FI20V**

**Specifications**

Charger voltage	100-240V~, 50-60Hz, 50W
Voltage	20V Li-Ion (2.0Ah)
No load speed	0-2.900/min.
Impact rate	0-3.300/min.
Chuck type	1/4" (6.35mm) Hex
Max. torque	150Nm
Machine weight	1.16 kg (without battery pack)

- Features**
- 4-pole Mabuchi® motor
  - Quick-change hex chuck
  - High-quality 2.0 Ah battery cells
  - 60 min. quick charger
  - Variable electronic speed control
  - LED light
  - Storage case



Includes 2 Li-Ion 2.0 Ah batteries - 2 Screwdriver bits - Quick charger  
Optional Accessories Battery CDA1132P, CDA1133P, CDA1148P  
Optional Accessories Charger CDA1131P, CDA1147P  
Availability Ex-works + FOB

**CORDLESS LI-ION DRILL**  
**20V CDM1144P**

**FI20V**

**Specifications**

Voltage	20V
No load speed position I	0-450/min.
No load speed position II	0-1.700/min.
Chuck capacity	Ø1.5-13mm
Torque positions	21+1
Max. torque (hard)	50Nm
Machine weight	1.24kg (without battery pack)

- Features**
- 4-pole Mabuchi® motor
  - Metal Jacobs® chuck
  - Variable electronic speed control
  - LED light
  - Storage case



Includes 2 Screwdriver bits  
Optional Accessories Battery CDA1132P, CDA1133P, CDA1148P  
Optional Accessories Charger CDA1131P, CDA1147P  
Availability Available on request

**CORDLESS LI-ION DRILL**  
**20V - 2.0AH CDM1141P**

**FI20V**

**Specifications**

Charger voltage	100-240V~, 50-60Hz, 50W
Voltage	20V Li-Ion (2.0Ah)
No load speed position I	0-450/min.
No load speed position II	0-1.700/min.
Chuck capacity	Ø1.5-13mm
Torque positions	21+1
Max. torque (hard)	50Nm
Machine weight	1.24kg (without battery pack)

- Features**
- 4-pole Mabuchi® motor
  - Metal Jacobs® chuck
  - High-quality 2.0 Ah battery cells
  - 60 min. quick charger
  - Variable electronic speed control
  - LED light
  - Storage case



Includes 2 Li-Ion 2.0 Ah batteries - 2 Screwdriver bits - Quick charger  
Optional Accessories Battery CDA1132P, CDA1133P, CDA1148P  
Optional Accessories Charger CDA1131P, CDA1147P  
Availability Ex-works + FOB

**BATTERY**  
**20V - 2.0AH CDA1132P**

**FI20V**

**Specifications**

Voltage	20V
Ampere hour	2.0Ah
Battery type	Li-Ion
Charging time	45 min. (With CDA1147P)
Charging time	60 min. (With CDA1131P)
Battery weight	0.38 kg

- Features**
- High-quality battery cells
  - Battery charge indication
  - Softgrip



Availability Available on request

**BATTERY**  
**20V - 4.0AH CDA1133P**

**FI20V**

**Specifications**

Voltage	20V
Ampere hour	4.0Ah
Battery type	Li-Ion
Charging time	60 min. (With CDA1147P)
Charging time	90 min. (With CDA1131P)
Battery weight	0.65 kg

- Features**
- High-quality battery cells
  - Battery charge indication
  - Softgrip



Availability Available on request

**BATTERY**  
**20V - 6.0AH CDA1148P**

**FI20V**

**Specifications**

Voltage	20V
Ampere hour	6.0Ah
Battery type	Li-Ion
Charging time	90 min. (With CDA1147P)
Battery weight	0.92 kg

- Features**
- High-quality battery cells
  - Battery charge indication
  - Softgrip



Availability Available on request

**QUICK CHARGER**  
**20V - 2.0A CDA1131P**

**FI20V**

**Specifications**

Charger input 100-240V~, 50-60Hz, 50W  
Charger output 20V 2A  
Charger weight 0.36 kg

**Features**

- Charge indication
- Charging time with CDA1132P 60 minutes
- Charging time with CDA1133P 90 minutes



Optional Accessories Battery CDA1132P, CDA1133P  
Availability Available on request

**QUICK CHARGER**  
**20V - 4.0A CDA1147P**

**FI20V**

**Specifications**

Charger input 100-240V~, 50-60Hz, 98W  
Charger output 20V 4A  
Charger weight 0.53 kg

**Features**

- Charge indication
- Charging time with CDA1132P 45 minutes
- Charging time with CDA1133P 60 minutes
- Charging time with CDA1148P 90 minutes



Optional Accessories Battery CDA1132P, CDA1133P, CDA1148P  
Availability Available on request

**ELECTRIC DRILL**  
**230W - 6.5MM PDM1047P**

**Specifications**

Mains voltage 220-240V~, 50Hz  
Power input 230W  
No load speed 0-4.500/min.  
Chuck capacity Ø0.5- 6.5mm  
Machine weight 1.20kg

**Features**

- Single function (drilling)
- Compact design
- Left/right rotation
- Variable electronic speed control
- 3m rubber cable



Includes Chuck key  
Availability Available on request

**ELECTRIC DRILL**  
**450W - 10MM PDM1048P**

**Specifications**

Mains voltage 220-240V~, 50Hz  
Power input 450W  
No load speed 0-3.300/min.  
Chuck capacity Ø1.5-10mm  
Machine weight 1.50kg

**Features**

- Single function (drilling)
- Left/right rotation
- Variable electronic speed control
- 3m rubber cable



Includes Chuck key  
Availability Ex-works + FOB

**ELECTRIC DRILL**  
**650W - 13MM PDM1059P**

**Specifications**

Mains voltage 220-240V~, 50-60Hz  
Power input 650W  
No load speed 0-3.000/min.  
Chuck capacity Ø1.5-13mm  
Machine weight 1.82kg

**Features**

- Left/right rotation
- Single function (drilling)
- Variable electronic speed control
- 3m rubber cable



Includes Chuck key  
Availability Available on request

**ELECTRIC DRILL**  
**650W - 13MM PDM1059P\_K**

**Specifications**

Mains voltage 220-240V~, 50-60Hz  
Power input 650W  
No load speed 0-3.000/min.  
Chuck capacity Ø1.5-13mm  
Machine weight 1.82kg

**Features**

- Keyless metal chuck
- Left/right rotation
- Single function (drilling)
- Variable electronic speed control
- 3m rubber cable



Availability Available on request

**IMPACT DRILL**  
**710W - 13MM PDM1049P**

**Specifications**

Mains voltage 220-240V~, 50Hz  
Power input 710W  
No load speed 0-3.200/min.  
Impact rate 0-51.200/min.  
Chuck capacity Ø1.5-13mm  
Machine weight 2.00kg

**Features**

- Double function (drilling and impact drilling)
- Variable electronic speed control
- Side handle with metal depth limiter
- 3m rubber cable



Includes Chuck key - Auxiliary handle - Metal depth limiter  
Availability Ex-works + FOB

**IMPACT DRILL**  
**710W - 13MM PDM1049P\_K**

**Specifications**

Mains voltage 220-240V~, 50Hz  
Power input 710W  
No load speed 0-3.200/min.  
Impact rate 0-51.200/min.  
Chuck capacity Ø1.5-13mm  
Machine weight 2.00kg

**Features**

- Keyless metal chuck
- Double function (drilling and impact drilling)
- Variable electronic speed control
- Side handle with metal depth limiter
- 3m rubber cable



Includes Auxiliary handle - Metal depth limiter  
Availability Ex-works + FOB

**IMPACT DRILL**  
**850W - 13MM PDM1060P**

**Specifications**

Mains voltage 220-240V~, 50/60Hz  
Power input 850W  
No load speed 0-3.000/min.  
Impact rate 0-48.000/min.  
Chuck capacity Ø1.5-13mm  
Machine weight 2.08kg

**Features**

- Double function (drilling and impact drilling)
- Variable electronic speed control
- Side handle with metal depth limiter
- 3m rubber cable
- Storage case



Includes Chuck key - Auxiliary handle - Metal depth limiter  
Availability Available on request

**IMPACT DRILL**  
**850W - 13MM PDM1060P\_K**

**Specifications**

Mains voltage 220-240V~, 50/60Hz  
Power input 850W  
No load speed 0-3.000/min.  
Impact rate 0-48.000/min.  
Chuck capacity Ø1.5-13mm  
Machine weight 2.08kg

**Features**

- Keyless metal chuck
- Double function (drilling and impact drilling)
- Variable electronic speed control
- Side handle with metal depth limiter
- 3m rubber cable
- Storage case



Includes Auxiliary handle - Metal depth limiter  
Availability Ex-works + FOB

**IMPACT DRILL**  
**1100W - 13MM PDM1061P**

**Specifications**

Mains voltage 220-240V~, 50/60Hz  
Power input 1.100W  
Mechanical speeds 2  
No load speed 0-1.200/min.  
0-3.100/min.  
Impact rate 0-19.200/min.  
0-49.600/min.  
Chuck capacity Ø1.5-13mm  
Machine weight 3.28kg

**Features**

- Double function (drilling and impact drilling)
- Mechanical 2 speed gearbox
- Metal gear housing
- Variable electronic speed control
- Side handle with metal depth limiter
- 3m rubber cable
- Storage case



Includes Chuck key - Auxiliary handle - Metal depth limiter  
Availability Available on request

**IMPACT DRILL**  
**1100W - 13MM PDM1061P\_K**

**Specifications**

Mains voltage 220-240V~, 50/60Hz  
Power input 1.100W  
Mechanical speeds 2  
No load speed 0-1.200/min.  
0-3.100/min.  
Impact rate 0-19.200/min.  
0-49.600/min.  
Chuck capacity Ø1.5-13mm  
Machine weight 3.28kg

**Features**

- Keyless metal chuck
- Double function (drilling and impact drilling)
- Mechanical 2 speed gearbox
- Metal gear housing
- Variable electronic speed control
- Side handle with metal depth limiter
- 3m rubber cable
- Storage case



Includes Auxiliary handle - Metal depth limiter  
Availability Ex-works + FOB

**ROTARY HAMMER**  
**800W - 3.3KG HDM1038P**

**Specifications**

Mains voltage	220-240V~, 50Hz
Power input	800W
No load speed	0-1.250/min.
Impact rate	0-5.500/min.
Chuck size	SDS-plus
Impact energy	2.7 Joule
Machine weight	3.30kg



**Features**

- 4 Functions (drilling, hammer drilling, chiseling, free rotation chiseling)
- Universal SDS-plus chuck
- Variable electronic speed control
- 3m rubber cable
- Storage case

Includes Auxiliary handle - Metal depth limiter - 3 SDS concrete drills - Chisel pointed - Chisel flat  
Availability Ex-works + FOB

**ROTARY HAMMER**  
**1100W - 6.6KG HDM1043P**

**Specifications**

Mains voltage	220-240V~, 50Hz
Power input	1.100W
No load speed	300-760/min.
Impact rate	1.950-4.860/min.
Chuck size	SDS-max
Impact energy	1-7 Joule
Machine weight	6.60kg
Drilling capacity	35mm



**Features**

- 3 Functions (hammer drilling, chiseling, free rotation chiseling)
- SDS-max chuck
- Soft start
- Variable electronic speed control
- Vibration reduction rear handle
- 5m rubber cable
- Storage case

Includes Auxiliary handle - Depth limiter  
Availability Ex-works + FOB

**JIG SAW**  
**750W JSM1025P**

**Specifications**

Mains voltage	230-240V~, 50Hz
Power input	750W
No load speed	500-3.000/min.
Bevel adjustment	0-45°
Machine weight	3.30kg



**Features**

- Variable electronic speed control
- Toolless saw blade exchange
- 4 pendulum positions
- Variable angle adjustment (0-45°)
- 4m rubber cable
- Storage case

Includes Saw blade wood - Splinter plate - Vacuum cleaner adapter - Anti-scratch plate - Parallel guide  
Availability Ex-works + FOB

**CIRCULAR SAW**  
**2200W - 235MM CSM1042P**

**Specifications**

Mains voltage	220-240V~, 50Hz
Power input	2.200W
No load speed	3.900/min.
Saw blade diameter	Ø235mm
Saw blade bore	Ø30mm
Bevel adjustment	0-45°
Machine weight	7.00kg



**Features**

- Angle and depth adjustment
- Spindle lock
- Lock-off safety switch
- High quality blade included
- 3m rubber cable

Includes Saw blade 235mm - Hexagon key - Parallel guide  
Availability Available on request

**DEMOLITION HAMMER**  
**1200W - 6.2KG HDM1040P**

**Specifications**

Mains voltage	220-240V~, 50Hz
Power input	1.200W
Impact rate	3.100/min.
Chuck size	SDS-max
Impact energy	14 Joule
Machine weight	6.20kg



**Features**

- Single function (chiselling)
- SDS-max chuck
- Powerful lightweight machine (14 joule - 6.2kg)
- 12 step adjustable chisel position
- Vibration reduction rear handle
- 5m rubber cable
- Storage case

Includes Auxiliary handle - Chisel pointed - Chisel flat  
Availability Ex-works + FOB

**DEMOLITION HAMMER**  
**1500W - 11KG HDM1049P**

**Specifications**

Mains voltage	220-240V~, 50Hz
Power input	1.500W
Impact rate	1.000-1.900/min.
Chuck size	SDS-max
Impact energy	6-25 Joule
Machine weight	11.00kg



**Features**

- Single function (chiselling)
- SDS-max chuck
- Powerful heavy duty machine (6 - 25 joule - 11.0kg)
- 12 step adjustable chisel position
- Vibration reduction rear handle
- 5m rubber cable
- Storage case

Includes Auxiliary handle - Chisel pointed - Chisel flat  
Availability Ex-works + FOB

**ORBITAL SANDER**  
**220W - 1/4 SHEET PSM1028P**

**Specifications**

Mains voltage	220-240V~, 50Hz
Power input	220W
No load speed	15.000/min.
Sanding surface	105x113mm
Paper size	140x114mm
Machine weight	1.40kg



**Features**

- Aluminum Velcro® base plate
- Paper clamping system
- Active dust extraction
- Softgrip
- 4m rubber cable

Includes Dust bag - Sanding sheet (Velcro®) - Perforation plate  
Availability Ex-works + FOB

**ORBITAL SANDER**  
**350W - 1/3 SHEET PSM1029P**

**Specifications**

Mains voltage	220-240V~, 50Hz
Power input	350W
No load speed	13.000/min.
Sanding surface	93x185mm
Paper size	93x230mm
Machine weight	2.00kg



**Features**

- Aluminum Velcro® base plate
- Paper clamping system
- Active dust extraction
- Softgrip
- 4m rubber cable

Includes Dust bag - Sanding sheet (Velcro®) - Perforation plate  
Availability Ex-works + FOB

**DEMOLITION HAMMER**  
**1500W - 16KG HDM1042P**

**Specifications**

Mains voltage	230V~, 50Hz
Power input	1.500W
Impact rate	1.400/min.
Chuck size	Hex 30mm
Impact energy	50 Joule
Machine weight	16.00kg



**Features**

- Single function (chiselling)
- Hex 30mm chuck
- Powerful heavy duty machine (50 joule - 16kg)
- Vibration reduction rear handle
- 5m rubber cable
- Storage case (with transport wheels)

Includes Auxiliary handle - Chisel pointed - Chisel flat  
Availability Ex-works + FOB

**JIG SAW**  
**450W JSM1028P**

**Specifications**

Mains voltage	220-240V~, 50Hz
Power input	450W
No load speed	0-3.400/min.
Bevel adjustment	0-45°
Machine weight	2.10kg



**Features**

- Variable electronic speed control
- 4 pendulum positions
- Variable angle adjustment (0-45°)
- 3m rubber cable
- Storage case

Includes Saw blade wood - Saw blade steel  
Availability Ex-works + FOB

**ORBITAL SANDER**  
**520W - 1/2 SHEET PSM1030P**

**Specifications**

Mains voltage	220-240V~, 50Hz
Power input	520W
No load speed	10.000/min.
Sanding surface	114x234mm
Paper size	114x278mm
Machine weight	2.70kg



**Features**

- Aluminum base plate
- Paper clamping system
- Powerful motor
- 4m rubber cable

Includes Sanding sheet  
Availability Available on request

**HOT AIR GUN**  
**2000W HAM1017P**

**Specifications**

Mains voltage	220-240V~, 50Hz
Power input	2.000W
Temperature setting	Variable
Temp/air volume setting 1:	50°C
Temp/air volume setting 2:	(250L/min.) 50°-450°C
Temp/air volume setting 3:	(250L/min.) 90°-600°C
Machine weight	(500L/min.) 0.90kg



**Features**

- Overheat protection
- Ceramic heating elements
- 3 Air speed settings
- Constant temperature control, adjustable by dial wheel
- 3m rubber cable

Availability Ex-works + FOB

**ROUTER**  
**2200W - 12MM PRM1019P**

**Specifications**

Mains voltage	220-240V~, 50Hz
Power input	2.200W
No load speed	9.000-22.000/min.
Collet size	Ø12mm
Machine weight	5.80kg



- Features**
- Heavy duty stable base plate
  - Suitable for 6mm, 8mm and 12mm router bits
  - Accurate depth adjustment with revolver setting
  - Electronic variable speed control
  - Spindle lock
  - 3m rubber cable

Includes Router bit - Parallel guide - Roller guide - Template guide - Wrench - Collet Ø6mm - Collet Ø8mm - Collet Ø12mm  
Availability Ex-works + FOB

**TRIMMER**  
**550W - 6MM PRM1020P**

**Specifications**

Mains voltage	220-240V~, 50Hz
Power input	550W
No load speed	35.000/min.
Collet size	Ø6mm
Machine weight	1.60kg



- Features**
- Compact design
  - Easy to adjust
  - Transparent base for good visibility
  - 3m rubber cable

Includes Router bit - Parallel guide - Edge guide - Template guide - Wrench - Collet Ø6mm  
Availability Available on request

**WALL CHASER**  
**2400W - 150MM WCM1001P**

**Specifications**

Mains voltage	230V~, 50Hz
Power input	2.400W
Disc diameter	150mm
No load speed	8.000/min.
Spindle	22.2mm
Cutting depth	0-43mm
Cutting width	30mm
Machine weight	6.10kg



- Features**
- Efficient wall chasing without chiselling due to 3-in-1 blades
  - Toolless adjustment of cutting depth
  - Dust extraction system
  - Metal support rollers
  - Spindle lock
  - Storage case
  - 4m rubber cable

Includes Spanners - 3-in-1 blade  
Optional Accessories WCA1001 Wall chaser blade 3-in-1 (150x22.2mm)  
Availability Ex-works + FOB

**MARBLE CUTTER**  
**1400W - 125MM MCM1008P**

**Specifications**

Mains voltage	220-240V~, 50/60Hz
Power input	1.400W
Disc diameter	125mm
No load speed	12.000 /min.
Disc bore	Ø20mm
Machine weight	3.20kg



- Features**
- Dust protected lock-on switch
  - For wet and dry use
  - Adjustable cutting depth
  - 2m cable

Includes Diamond disc - Hexagon key - Wrench - Water line set  
Availability Available on request

**ANGLE POLISHER**  
**1400W - 180MM AGM1120P**

**Specifications**

Mains voltage	220-240V~, 50Hz
Power input	1.400W
Disc diameter	180mm
No load speed	1.000-3.300/min.
Spindle	M14
Machine weight	3.10kg



- Features**
- Variable electronic speed control
  - Constant speed electronics
  - Lock-on switch
  - Spindle lock
  - 4m rubber cable

Includes Front handle - Hexagon key - Base plate (Velcro®) - Polishing foam pad - Polishing wool pad - Nylon accessory bag  
Optional Accessories AGA1033P Polish set 180mm 2 pcs  
Availability Ex-works + FOB





**[WWW.FERM-INDUSTRIAL.COM](http://WWW.FERM-INDUSTRIAL.COM)**

2204-21