FERM®

POWER SINCE 1965

CATALOG

DESIGNED AND DEVELOPED IN THE NETHERLANDS

CORDLESS LI-ION SCREWDRIVER
3.6V - 1.3AH CDM1132

Specifications

Mains voltage (charger)	100-240V~, 50/60Hz
Power input	3.6V-1.3AH
Max. torque	4Nm
No load speed	230/min.
Charging time	3-5 hours



Features
- Cordless, Li-ion technology
- Spindle lock
- LED work light
- Magnetic chuck 1/4”
- Metal storage case

Includes	27 pcs accessory set - Charger adapter
Availability	Ex-works + FOB

CORDLESS LI-ION DRILL
12V - 1.5AH CDM1119

Specifications

Mains voltage (charger)	100-240V~, 50/60Hz
Power input	12V-1.5Ah
Max. torque (hard)	20Nm
No load speed position I	0-350/min.
No load speed position II	0-1.300/min.
Number of torque positions	17+1
Charging time	1 hour



Features
- Cordless, Li-Ion technology
- 2 Batteries
- LED work light
- Single sleeve chuck 1.0-10mm
- Adjustable torque settings
- Two mechanical speed settings
- Variable electronic speed control
- Storage case

Includes	2 Li-Ion batteries (12V-1.5Ah) - 2 Double sided 50mm bits (S2) - Charger
Optional Accessories	Battery CDA1142
Availability	Ex-works + FOB

CORDLESS LI-ION DRILL
18V - 1.5AH CDM1120

Specifications

Mains voltage (charger)	100-240V~, 50/60Hz
Power input	18V-1.5Ah
Max. torque (hard)	32Nm
No load speed position I	0-350/min.
No load speed position II	0-1.300/min.
Number of torque positions	17+1
Charging time	1 hour



Features
- Cordless, Li-Ion technology
- 2 Batteries
- LED work light
- Single sleeve chuck 1.5-13mm
- Adjustable torque settings
- Two mechanical speed settings
- Variable electronic speed control
- Storage case

Includes	2 Li-Ion batteries (18V-1.5Ah) - 2 Double sided 50mm bits (S2) - Charger
Optional Accessories	Battery CDA1144
Availability	Ex-works + FOB

CORDLESS LI-ION IMPACT WRENCH
18V - 4.0AH CDM1127

Specifications

Mains voltage (charger)	100-240V~, 50/60Hz
Power input	18V-4.0Ah
Max torque	380Nm
No load speed	0-2.300/min.
Charging time	3-5 hours



Features
- Cordless, Li-Ion technology
- ½” square drive shaft
- LED work light
- Variable electronic speed
- Soft grip
- Storage case

Includes	Li-Ion battery (18V-4.0Ah) - Socket 19mm - Socket 21mm - Charger
Optional Accessories	Battery CDA1096
Availability	Ex-works + FOB

CORDLESS COMBI DRILL BRUSHLESS
20V - 2.0AH CDM1138

Specifications

Charger voltage	230-240V~, 50Hz
Voltage	20V Li-Ion (2.0Ah)
Max. torque (hard)	32Nm
No load speed position I	0-550/min.
No load speed position II	0-2.000/min.
No load impact rate position I	0-8.250/min
No load impact rate position II	0-30.000/min
Number of torque positions	25+drill+impact
Charging time	1 hour



Features
- Cordless, Li-Ion technology
- 2 Batteries
- Brushless motor
- 3 operating modes: Screwing, drilling, impact drilling
- LED work light
- Single sleeve metal chuck 2-13mm
- Adjustable torque settings
- Two mechanical speed settings
- Variable electronic speed control
- Side handle with soft grip
- Storage case

Includes	2 Li-Ion batteries (20V-2.0Ah) - 2 Screwdriver bits - Charger
Optional Battery	CDA1130
Availability	Ex-works + FOB

IMPACT DRILL
550W PDM1051

Specifications

Mains voltage	220-240V~, 50Hz
Power input	550W
No load speed	0-3.000/min.
No load impact rate	0-48.000/min.
Chuck capacity	2-13mm



Features
- Double function (drilling and impact drilling)
- Depth limiter
- Variable electronic speed control
- Lock-on switch
- 3m rubber cable

Includes	Side handle - Depth limiter
Availability	Ex-works + FOB

IMPACT DRILL
800W PDM1052

Specifications

Mains voltage	230V~, 50Hz
Power input	800W
No load speed	0-3.000/min.
No load impact rate	0-48.000/min.
Chuck capacity	2-13mm



Features
- Double function (drilling and impact drilling)
- Depth limiter
- Variable electronic speed control
- Lock-on switch
- 3m rubber cable

Includes	Side handle - Depth limiter
Availability	Ex-works + FOB

ROTARY HAMMER
850W HDM1028

Specifications

Mains voltage	230-240V~, 50/60Hz
Power input	850W
No load speed	900/min.
No load impact rate	4.000/min.
Impact energy	4.5 Joule
Chuck size	SDS-plus



Features
- 3 Functions (dilling, hammer drilling, chiseling)
- Universal SDS-plus toolholder
- 3m cable
- Storage case

Includes	Side handle - Dust cover - Grease tube - Depth gauge - 3 SDS concrete drills (8mm, 10mm, 12mm) - Chisel pointed (250mm) - Chisel flat (250mm) - Grease cover - Wrench
Availability	Ex-works + FOB

ROTARY HAMMER
1500W HDM1037

Specifications

Mains voltage	230V~, 50Hz
Power input	1.500W
No load speed	0-950/min.
No load impact rate	0-4.400/min.
Impact energy	6.0 Joule
Chuck size	SDS-plus



Features
- 4 Functions (drilling, hammer drilling, free rotation chiseling, chiseling)
- Universal SDS-plus toolholder
- Variable electronic speed control
- 3m cable
- Storage case

Includes	Side handle - Dust cover - Grease tube - Depth gauge - 3 SDS concrete drills (8mm, 10mm, 12mm) - Chisel pointed (250mm) - Chisel flat (250mm) - Grease cover - Wrench
Availability	Ex-works + FOB

ANGLE GRINDER
500W - 115MM AGM1086

Specifications

Mains voltage	230V~, 50Hz
Power input	500W
No load speed	11.000/min.
Disc diameter	115mm
Spindle	M14



Features
- Lock-on switch
- Spindle lock
- Adjustable open safety guard
- Electronic restart protection
- 3m cable

Includes	Side handle - Wrench
Availability	Ex-works + FOB

ANGLE GRINDER
850W - 125MM AGM1087

Specifications

Mains voltage	230V~, 50Hz
Power input	850W
No load speed	11.000/min.
Disc diameter	125mm
Spindle	M14



Features
- Lock-on switch
- Spindle lock
- Adjustable open safety guard
- Electronic restart protection
- 3m cable

Includes	Side handle - Wrench
Availability	Ex-works + FOB

ANGLE GRINDER
900W - 125MM AGM1061S

Specifications

Mains voltage	230-240V~, 50Hz
Power input	900W
No load speed	12.000/min.
Disc diameter	125mm
Spindle	M14



Features
- Paddle switch
- 3 Side handle positions
- Spindle lock
- Adjustable open safety guard with quick release
- 3m rubber cable

Includes	Side handle - Wrench
Availability	Ex-works + FOB

ANGLE GRINDER
2500W - 230MM AGM1088

Specifications

Mains voltage	230-240V~, 50Hz
Power input	2.500W
No load speed	6.500/min.
Disc diameter	230mm
Spindle	M14



Features
- Lock-off safety switch
- Spindle lock
- Adjustable open safety guard
- Soft start
- 3 Side handle positions
- 3m rubber cable

Includes	Side handle - Wrench - Hexagonal key
Availability	Ex-works + FOB

CORDLESS LI-ION JIG SAW
12V - 1.5AH JSM1026

Specifications

Mains voltage (charger)	100-240V~, 50/60Hz
Power input	12V-1.5Ah
No load speed	2.100/min.
Charging time	3-5 hours



Features
- Cordless, Li-Ion technology
- Quick release blade holder
- Universal, suitable for T & U shank blades
- Soft grip
- Storage case

Includes	Li-Ion battery (12V-1.5Ah) - Saw blade (wood) - Saw blade (metal) - Charger
Optional Accessories	Battery CDA1094 - Jig saw blades 10pcs JSA1004
Availability	Ex-works + FOB

JIG SAW
570W JSM1023

Specifications

Mains voltage	230V~, 50Hz
Input power	570W
No load speed	500-3.000/min.
Bevel adjustment	0-45°
Saw stroke	18mm
Saw capacity wood max.	70mm
Saw capacity steel max.	6mm



Features
- Lock-on switch
- Electronic variable speed
- 4 Pendulum positions
- Variable bevel cut adjustment to 45°
- Dust extraction outlet
- 3m cable

Includes	Parallel guide - Hexagonal key - Vacuum cleaner adapter - 4 T-shank saw blades
Optional Accessories	Jig saw blades 10pcs JSA1004
Availability	Ex-works + FOB

JIG SAW
710W JSM1014

Specifications

Mains voltage	230V~, 50Hz
Input power	710W
No load speed	800-3.000/min.
Bevel adjustment	0-45°
Saw stroke	20mm
Saw capacity wood max.	110mm
Saw capacity steel max.	10mm



Features
- Lock-on switch
- Electronic variable speed
- 4 Pendulum positions
- Variable bevel cut adjustment to 45°
- Dust extraction outlet
- 3m cable

Includes	Parallel guide - Hexagonal key - Vacuum cleaner adapter - 3 T-shank saw blades
Optional Accessories	Jig saw blades 10pcs JSA1004
Availability	Ex-works + FOB

RECIPROCATING SAW
710W RSM1019

Specifications

Mains voltage	230-240V~, 50Hz
Input power	710W
No load speed	0-2.800/min.
Saw stroke	20mm



Features
- Lock-on switch
- Electronic variable speed
- Toolless saw blade release
- Adjustable front plate
- 3m rubber cable

Includes	Hexagonal key - 2 Saw blades
Optional Accessories	Reciprocating blades 9pcs RSA1001
Availability	Ex-works + FOB

PRECISION CIRCULAR SAW
500W CSM1043

Specifications

Mains voltage	220-240V~, 50Hz
Input power	500W
No load speed	3.500-6.500/min.
Saw blade diameter	85mm
Saw blade bore	15mm
Cutting depth	0-22mm



Features
- Variable speed
- Adjustable sawing depth
- 3pcs saw blade set included
- Side handle
- Dust extraction outlet
- 3m rubber cable
- Storage case

Includes	TCT saw blade T24 - HSS saw blade T44 - Diamond saw blade - Dust extraction adapter - Hexagonal key - Guide ruler - Handle
Optional Accessories	Precision saw blade CSA1046 - CSA1047 (24T-TCT) - CSA1048 (44T-HSS) - CSA1049 Guide rail set
Availability	Ex-works + FOB

PRECISION CIRCULAR SAW
500W CSM1043_S

Specifications

Mains voltage	220-240V~, 50Hz
Input power	500W
No load speed	3.500-6.500/min.
Saw blade diameter	85mm
Saw blade bore	15mm
Cutting depth	0-22mm



Features
- Variable speed
- Adjustable sawing depth
- 3pcs saw blade set included
- Side handle
- Dust extraction outlet
- 3m rubber cable
- Storage case
- 700mm guide rail set

Includes	TCT saw blade T24 - HSS saw blade T44 - Diamond saw blade - Dust extraction adapter - Hexagonal key - Guide ruler - Handle - CSA1049 Guide rail set
Optional Accessories	Precision saw blade CSA1046 - CSA1047 (24T-TCT) - CSA1048 (44T-HSS) - CSA1049 Guide rail set
Availability	Ex-works + FOB

CIRCULAR SAW
1200W - 185MM CSM1039

Specifications

Mains voltage	230-240V~, 50Hz
Input power	1.200W
Bevel adjustment	0-45°
No load speed	5.000/min.
Saw blade diameter	185mm
Saw blade bore	20mm
Cutting depth max.	65mm (90°)
Cutting depth max.	43mm (45°)



Features
- Angle and depth adjustment
- Parallel guide
- Spindle lock
- 3m rubber cable

Includes	Hexagonal key - Parallel guide - TCT saw blade 185mm T24
Optional Accessories	Saw blade CSA1007 (T24)
Availability	Ex-works + FOB

WALL SLOTTER
1700W - 125MM WSM1009

Specifications

Mains voltage	230-240V~, 50Hz
Input power	1.700W
No load speed	4.000/min.
Cutting depth	0-28mm
Cutting width	14-19-29mm
Disc diameter	125mm



Features
- Overload protection
- Soft start
- Spindle lock
- Laser guidance
- Adjustable cutting depth and width
- 3m cable
- Storage case

Includes	2 Diamond discs - Universal vacuum cleaner adapter - Chisel - Hexagonal key - Batteries for laser
Optional Accessories	Saw blade set 2pcs WSA1001 (125mm open)
Availability	Ex-works + FOB

WALL SLOTTER
1600W - 150MM WSM1008

Specifications

Mains voltage	230V~, 50Hz
Input power	1.600W
No load speed	6.000/min.
Cutting depth	5-40mm
Cutting width	8-30mm
Disc diameter	150mm



Features
- Overload protection
- Soft start
- Power feedback
- Spindle lock
- Laser guidance
- Adjustable cutting depth and width
- 3m cable
- Canvas storage bag

Includes	2 Diamond discs - Universal vacuum cleaner adapter - Chisel - Batteries for laser
Optional Accessories	Saw blade set 2pcs WSA1002 (150mm open)
Availability	Ex-works + FOB

PAINT/CEMENT MIXER
1400W PMM1006

Specifications

Mains voltage	230V~, 50Hz
Input power	1.400W
No load speed (I)	180-380/min.
No load speed (II)	300-650/min.



Features
- Lock-on switch
- Variable electronic speed control
- Two mechanical speed settings
- Whisk included
- 3m rubber cable

Includes	Whisk for general purposes - 2 Wrenches
Optional Accessories	Whisk PMA1004 - Whisk PMA1008
Availability	Ex-works + FOB

DETAIL SANDER
220W PSM1013

Specifications

Mains voltage	230V~, 50Hz
Input power	220W
No load speed	13.000/min.
Sanding movements	26.000/min.
Sanding paper size	145x145x88mm triangle shape



Features
- Hook & Loop base plate
- Active dust extraction
- 3m cable
- Storage case

Includes	5 Sanding papers (P80) - 5 Sanding papers (P120) - Dust bag
Optional Accessories	Sanding paper set 5pcs PSA1007 (P80) - PSA1008 (P120)
Availability	Ex-works + FOB

ORBITAL SANDER
135W PSM1027

Specifications

Mains voltage	230V~, 50Hz
Input power	135W
No load speed	13.000/min.
Sanding surface	90x187mm



Features
- Hook & Loop base plate
- Paper clamping system
- Universal vacuum cleaner adapter
- 3m rubber cable

Includes	Sanding paper (P80) - Vacuum cleaner adapter
Availability	Ex-works + FOB

ORBITAL SANDER
180W PSM1024

Specifications

Mains voltage	230V~, 50Hz
Input power	180W
No load speed	12.000/min.
Sanding movements	24.000/min.
Sanding surface	90x187mm



Features
- Aluminum Hook & Loop base plate
- Paper clamping system
- Universal vacuum cleaner adapter
- 3m cable

Includes	5 Sanding papers (P80) - 5 Sanding papers (P120) - Vacuum cleaner adapter
Optional Accessories	Sanding paper set 5pcs PSA1031 P60 P80 P120
Availability	Ex-works + FOB

DELTA SANDER
280W DSM1009

Specifications

Mains voltage	230-240V~, 50Hz
Input power	280W
No load speed	6.000-11.000/min.
Sanding movements	12.000-22.000/min.
Sanding surface	90x90x90mm



Features
- Hook & Loop base plate
- Electronic variable speed
- Universal vacuum cleaner adapter
- 3m cable

Includes	2 Sanding papers (P80 / wood) - 2 Sanding papers (P80 / paint) - 2 Sanding papers (P80 / stone) - Vacuum cleaner adapter - Protection cover for sanding pad nose
Optional Accessories	Sanding paper set 10pcs PSA1033 (P80) - PSA1034 (P120)
Availability	Ex-works + FOB

RANDOM ORBITAL SANDER
430W ESM1010

Specifications

Mains voltage	230-240V~, 50Hz
Input power	430W
No load speed	5.000-13.000/min.
Base plate diameter	125mm



Features
- Hook & Loop base plate
- Electronic variable speed
- 3m cable

Includes	Dust collection box - 2 Sanding papers (P60) - 2 Sanding papers (P80) - 2 Sanding papers (P120)
Availability	Ex-works + FOB

PRECISION BELT SANDER
400W EFM1001

Specifications

Mains voltage	230-240V~, 50Hz
Input power	400W
No load speed	1.070-1.650/min.
Belt length	455mm
Belt width	8 and 13mm



Features
- Electronic variable speed
- Quick release belt exchange
- 3m cable
- Storage case

Includes	Dust bag - Vacuum cleaner adapter - 3 Sanding arm (8mm, 13mm, 13mm angled) - 12 Sanding papers
Optional Accessories	Sanding belt set 8pcs P40, P80, P120 EFA1003 (10mm) - EFA1004 (13mm)
Availability	Ex-works + FOB

BELT SANDER
900W BSM1024

Specifications

Mains voltage	230V~, 50Hz
Input power	900W
Belt dimension	75x533mm
Sanding surface	75x135mm
Belt speed	380m/min.



Features
- Electronic variable speed
- Quick release belt exchange
- 3m cable

Includes	Sanding belt (P80) - Dust bag
Optional Accessories	Sanding belt set 3pcs P60, P80, P120 (BSA1013)
Availability	Ex-works + FOB

PLANER
650W PPM1010

Specifications

Mains voltage	230V~, 50Hz
Input power	650W
No load speed	16.500/min.
Max. planing width	82mm
Max. planing depth max	2mm



Features
- Lock-on switch
- Adjustable planing depth
- Reversible hard metal planing knives
- 3m cable

Includes	Parallel guide - Spare belt - Dust bag
Optional Accessories	Chisel set 2pcs 82mm PPA1003
Availability	Ex-works + FOB

ROUTER
1200W PRM1021

Specifications

Mains voltage	230-240V~, 50Hz
Power input	1200W
No load speed	9.000-30.000/min.
Max. cutting depth	35mm
Max. cutter diameter	32mm



Features
- Depth adjustment
- Electronic variable speed control
- Dust extraction connector
- Spindle lock
- 3m cable

Includes	Parallel guide - Centring pin - Template guide - Spanner - 3pcs bit set - 6mm+8mm collet
Optional Accessories	Router bit set 20pcs PRA1008 - Router table PRA1011
Availability	Ex-works + FOB

ROUTER
1300W PRM1015

Specifications

Mains voltage	230V~, 50Hz
Power input	1300W
No load speed	9.000-30.000/min.
Max. cutting depth	60mm
Max. cutter diameter	30mm



Features
- Accurate depth adjustment: 0.1mm
- Electronic variable speed control
- LED work light
- Lock-off switch in handle
- Dust extraction connector
- Spindle lock
- 3m cable

Includes	Parallel guide - Template guide - Wrench - Hexagonal key - 6pcs bit set - 6mm+8mm collet
Optional Accessories	Router bit set 20pcs PRA1008 - Router table PRA1011
Availability	Ex-works + FOB

ROUTER TABLE
PRA1011

Specifications

Mains voltage	230V~, 50Hz
Table size	455x330mm
Max. base plate diameter router	162mm



Features
- Safety switch
- Dust extraction port
- Adjustment plate
- Robust and stable aluminum construction, provided with rubber feet
- Fits all current FERM routers and most other routers

Includes	Fence - Featherboard - Vacuum cleaner adapter
Availability	Ex-works + FOB

PRECISION BISCUIT JOINTER
900W BJM1009

Specifications

Mains voltage	230V~, 50Hz
Input power	900W
No load speed	11.000/min.
Saw blade	100x22mm
Saw blade thickness	4mm
Cutting depth	0-14mm
Base adjustment	0°-90°
Biscuits size	0-10-20



Features
- For creating precise joints and sawing parquet along walls
- Easy adjustment for angle and material thickness
- Aluminum base plate
- Spindle lock function
- Storage case

Includes	Saw blade 100x22x4mm - Hexagon key - Dustbag - 50 Biscuits (#20)
Optional Accessories	Biscuits 50pcs 56x23x4mm BJA1004 - Saw blade BJA1005
Availability	Ex-works + FOB

CORDLESS LI-ION MULTI TOOL
12V - 1.5AH OTM1006

Specifications

Mains voltage (charger)	100-240V~, 50/60Hz
Power input	12V-1.5Ah
No load speed	5.000-18.000/min.
Oscillation angle	3.0°
Charging time	3-5 hours



Features
- Cordless, Li-Ion technology
- Universal blade connection
- Electronic variable speed
- Easy blade exchange
- Soft grip
- Storage case

Includes	Li-Ion battery (12V-1.5Ah) - 3 Sanding papers - Hook & Loop sanding base plate - HSS half round cutting blade - Plunge cutting blade - Scraping knife - Hexagon key
Optional Accessories	Battery CDA1094 - Plunge cutting blade OTA1001 - Scraping knife OTA1002 - Sanding pad OTA1003 - HSS segment saw blade OTA1004 - Carbide blade OTA1005 - Multi tool accessory set 4 pcs OTA1007
Availability	Ex-works + FOB

MULTI TOOL
280W OTM1005

Specifications

Mains voltage	230V~, 50Hz
Input power	280W
No load speed	11.000-20.000/min.
Oscillating angle	2.8°



Features
- Lock-on switch
- LED work light
- Universal vacuum cleaner adapter
- Electronic variable speed
- Easy blade exchange
- 3m cable
- Storage case

Includes	Vacuum cleaner adapter - 10 Sanding papers - Hook & Loop sanding base plate - HSS half round cutting blade - Plunge cutting blade - Scraping knife - Carbide saw blade - Hexagon key
Optional Accessoires	Plunge cutting blade OTA1001 - Scraping knife OTA1002 - Sanding pad OTA1003 - HSS segment saw blade OTA1004 - Carbide blade OTA1005 - Multi tool accessory set 4 pcs OTA1007
Availability	Ex-works + FOB

CORDLESS LI-ION COMBITOOL
12V - 1.5AH CTM1016

Specifications

Mains voltage (charger)	100-240V~, 50/60Hz
Power input	12V-1.5Ah
No load speed	3.000-20.000/min.
Charging time	3-5 hours



Features
- Cordless, Li-Ion technology
- Electronic variable speed
- Suitable for 2.4mm and 3.2mm accessories
- Soft grip
- Spindle lock
- Storage case

Includes	1 Li-Ion battery (12V-1.5Ah) - 43 Accessories - Collet Ø2.4mm - Collet Ø3.2mm - Wrench - Charger
Optional Accessories	Battery CDA1094 - Combitool set 100pcs CTA1007 - Combitool set 40pcs CTA1008
Availability	Ex-works + FOB

COMBITOOL
160W CTM1012

Specifications

Mains voltage	230V~, 50Hz
Input power	160W
No load speed	15.000-35.000/min.
Collet diameter	2.4 and 3.2mm



Features
- Electronic variable speed
- Spindle lock
- 3m cable
- Storage case

Includes	40 Accessories - Collet Ø2.4mm - Collet Ø3.2mm - Wrench
Optional Accessories	Combitool set 100pcs CTA1007 - Combitool set 40pcs CTA1008
Availability	Ex-works + FOB

COMBITOOL SET
160W CTM1010

Specifications

Mains voltage	230V~, 50Hz
Input power	160W
No load speed	15.000-35.000/min.
Collet diameter	2.4 and 3.2mm



Features
- Electronic variable speed
- Spindle lock
- 3m cable
- Flexible shaft
- Adjustable stand
- Desk stand
- Storage case

Includes	40 Accessories - Collet Ø2.4mm - Collet Ø3.2mm -Wrench
Optional Accessories	Combitool set 100pcs CTA1007 - Combitool set 40pcs CTA1008
Availability	Ex-works + FOB

HOT AIR GUN
2000W HAM1015

Specifications

Mains voltage	220-240V~, 50Hz
Input power	2.000W
Pos. I:	300 L/min. 450°C
Pos. II:	500 L/min. 600°C



Features
- Overheat protection
- Stationairy mode
- 2 Heat and air flow settings
- 3m cable
- Storage case

Includes	Fishtail diffuser - Deflector diffuser
Availability	Ex-works + FOB

ELECTRIC BLOWER
400W EBM1003

Specifications

Mains voltage	220-240V~, 50Hz
Input power	400W
No load speed	6.000-14.000/min
Max. air displacement	3.0m³/min
Blow pipe size	220x25mm



Features
- Lock-on switch
- Electronic variable speed
- Use as blower and vacuumcleaner
- 3m cable

Includes	Rubber blow pipe - Dust bag
Availability	Ex-works + FOB

ELECTRIC TACKER
MAX. 16MM ETM1004

Specifications

Mains voltage	230V~, 50Hz
Staple width	11.3mm
Staple length	8-16mm
Nail length	15-16mm



Features
- Impact control wheel
- Anti-jam mechanism
- Compact design
- Safety switch

Includes	400 Staples 14mm - 100 nails 15mm
Optional Accessories	Nails 1500pcs ETA1005 (15mm) - Staples 2000pcs ETA1009 (8mm) - Staples 2000pcs ETA1010 (14mm)
Availability	Ex-works + FOB

CORDLESS LI-ION GLUE GUN
7.2V - 1.5AH GGM1003

Specifications

Mains voltage (charger)	100-240V~, 50/60Hz
Power input	7.2V-1.5Ah
Runtime on 1 charge:	45min.
Charging time	1 hour
Glue stick size	Ø7mm



Features
- Cordless, Li-Ion technology
- Fast: 15s pre-heat time
- 170° C work temp.
- Automatic stop (after 5 minutes of inactivity)
- Soft grip
- Storage case

Includes	6 Glue sticks GGA1003 (7x150mm)
Availability	Ex-works + FOB

GLUE GUN
75W GGM1004

Specifications

Mains voltage	220-240V~, 50Hz
Rated power	25W
Max. power	75W
Glue stick diameter	11.2mm
Heat-up time	3-5 min
Glue flow	8-12g/min



Features
- Adjustable table stand
- Anti-drip control
- Insulated nozzle
- Protection side lifts

Includes	4 Glue sticks 150mm
Optional accessories	6 Glue sticks GGA1005 (11.2x100mm)
Availability	Ex-works + FOB

SOLDERING STATION
48W SGM1013

Specifications

Mains voltage	220-240V~, 50Hz
Input power	48W
Temperature	160°C - 480°C



Features
- Adjustable temperature
- Accessory drawer
- Overheat protection
- Mica heating element
- Replaceable tips
- Soft grip on bolt

Includes	Flat tip - Point tip - Sponge - Solder wire Ø1.0mm - Solder wire Ø1.5mm
Availability	Ex-works + FOB

SOLDERING / BLOW TORCH
MAX. 1500°C SGM1006

Specifications

Runtime on single fill	35min.
Max. flame temperature	1300°C
Max. soldering temperature	500°C



Features
- For precise soldering, shrinking, hot cutting, lighting your fireplace, for kitchen use etc.
- Suitable for standard lighter gas
- Storage case

Includes	Standard tip - Chisel tip - Diagonal tip - Hot blower tip - Hot knife tip - Scraper - 2 Wrenches - De-soldering sponge
Availability	Ex-works + FOB

MULTIPURPOSE SPRAY GUN
110W SGM1012

Specifications

Mains voltage	220-240V~, 50Hz
Input power	110W
Max flow	300ml/min.
Container	800ml



Features
- Adjustable flow control
- Easy cleaning
- Airless spray
- 3m cable

Includes	Paint container - Flexible nozzle extension - Spare nozzle - Viscosity measuring cup - Cleaning pin - Ear plugs - Wrench - Piston
Availability	Ex-works + FOB

BENCH PILLAR DRILL
350W TDM1026

Specifications

Mains voltage	230V~, 50Hz
Input power	350W
Chuck capacity	13mm
Taper of spindle	B16
No load speed	500-890-1.400-1.900-2.500/min.
Total height	600mm
Travel of spindle	52mm
Horizontal distance	104mm chuck to column



Features
- Cast iron base for maximum stability
- Key chuck (13mm)
- In height adjustable working table with two way angle adjustment from 0° to 45°
- Safety switch

Includes	Chuck key
Optional Accessories	Machine vise TDA1013
Availability	Ex-works + FOB

BENCH GRINDER
150W - 150MM BGM1019

Specifications

Mains voltage	230V~, 50Hz
Input power	150W
Grinding stone dimensions	150x16mm
Grinding stone grain	P36 & P60
Grinding stone bore	12.7mm
No load speed	2.950/min.



Features
- Dust protected switch
- Metal base
- Mountable to work bench

Includes	Grinding stones (P36 & P60) - 2 Spark arresters - 2 Work rests - Safety glasses
Optional Accessories	Grinding stone 150mm BGA1053 (16mm - P36) - BGA1054 (16mm - P60)
Availability	Ex-works + FOB

BENCH GRINDER
250W - 150MM BGM1020

Specifications

Mains voltage	230V~, 50Hz
Input power	250W
Grinding stone dimensions	150x20mm 150x40mm
Grinding stone grain	P36 (grey) P80 (white)
Grinding stone bore	12.7mm
No load speed	2.950/min.



Features
- Dust protected switch
- Metal base
- Mountable to work bench

Includes	Grinding stones (P36 & P80) - 2 Spark arresters - 2 Work rests - Safety glasses
Optional Accessories	Grinding stone 150mm BGA1055 (20mm - P36) - BGA1056 (40mm - P80)
Availability	Ex-works + FOB

WET AND DRY GRINDER
250W BGM1021

Specifications

Mains voltage	230V~, 50Hz
Input power	250W
Grinding stone dimensions	150x20mm 200x40mm
Grinding stone grain	P36 (dry) P80 (wet)
Grinding stone bore	12.7mm(dry) 20mm (wet)
No load speed	2.950/min(dry) 135/min(wet)



Features
- Dust protected switch
- Metal base
- Mountable to work bench

Includes	Grinding stones (P36 & P80) - 2 Spark arresters - 2 Work rests - Safety glasses
Optional Accessories	Grinding stone BGA1055 (150mm - 20mm - P36) - BGA1057 (200mm - 40mm - wet use)
Availability	Ex-works + FOB

BENCH SANDER
350W BGM1022

Specifications

Mains voltage	230-240V~, 50Hz
Input power	350W
Belt dimension	100x915mm
Disc diameter	150mm
Belt speed	292m/min.
Disc speed	1.450/min.
Belt position adjustable	0°-90°
Table position adjustable	0°-45°



Features
- Hook & Loop disc base
- Dust protected safety switch
- Adjustable sanding belt position
- Adjustable working table
- Quick release belt exchange
- Rubber feet
- 2pcs 32mm 90° vacuum cleaner adapters

Includes	2 Sanding belts (P80, P120) - 2 Sanding discs (P80, P120) - Mitre guide – 2 Hexagonal keys
Optional Accessories	Sanding belt set 3pcs BGA1058 (P60, P80, P150) - BGA1060 (P100) - Sanding disc set 10pcs BGA1062 (P60, P100, P150)
Availability	Ex-works + FOB

SCROLL SAW
120W SSM1007

Specifications

Mains voltage	230V~, 50Hz
Input power	120W
Bevel adjustment table	0-45°
Max. working depth	406mm
Max. Sawing capacity at 90°	50mm
Max. Sawing capacity at 45°	23mm
No load speed	400 - 1600/min



Features
- Safety switch
- Foot pedal switch
- Adjustable speed
- Quick blade tensioning
- Transparent guard
- Working table adjustable from 0-45°
- Flexible dust blower
- Vaccuum cleaner connection
- Rubber feet

Includes	2 Saw blades 10 TPI - 2 Saw blades 15 tpi - 2 Saw blades 25 TPI - 2 Saw blade adapters
Optional Accessories	Scroll saw blade set 5pcs SSA1001 (15TPI) - SSA1002 (10TPI) - SSA1003 (18TPI) - SSA1004 (25TPI)
Availability	Ex-works + FOB

RADIAL MITRE SAW
1500W - 210MM MSM1039

Specifications

Mains voltage	220-240V~, 50Hz
Power input	1.500W
No load speed	4.500/min.
	Max. saw capacity
Mitre 0°,bevel 0°	70x305mm
Mitre 0°,bevel 45°	35x305mm
Mitre 45°,bevel 0°	70x210mm
Mitre 45°,bevel 45°	35x210mm



Features
- Metal base plate
- Sliding fence
- Laser guidance
- Transparant saw blade cover
- Mountable to workbench
- Pre-settings for quick and accurate mitre-angle adjustment
- Table extensions

Includes	TCT saw blade 210x30mm T48 - Hexagonal key - Dust bag - Work piece clamp - 2 Extension bars
Optional Accessories	Saw blade 210mm MSA1024 (24T) - MSA1025 (40T)
Availability	Ex-works + FOB

RADIAL MITRE SAW
1900W - 254MM MSM1040

Specifications

Mains voltage	230-240V~, 50Hz
Power input	1.900W
No load speed	4.500/min.
	Max. saw capacity
Mitre 0°,bevel 0°	70x310mm
Mitre 0°,bevel 45°	40x310mm
Mitre 45°,bevel 0°	70x210mm
Mitre 45°,bevel 45°	40x210mm



Features
- Metal base plate
- Sliding fence
- Laser guidance
- Transparant saw blade cover
- Mountable to workbench
- Pre-settings for quick and accurate mitre-angle adjustment
- Table extensions

Includes	TCT saw blade 254x30mm T60 - Hexagonal key - Dust bag - Work piece clamp - 2 Extension bars
Optional Accessories	Saw blade 255mm MSA1028 (40T) - MSA1029 (72T)
Availability	Ex-works + FOB

TABLE SAW
800W - 200MM TSM1036

Specifications

Mains voltage	230-240V~, 50Hz
Input power	800W
No load speed	2.950/min.
Table size	505x373mm
Saw blade diameter	200mm
Saw blade bore	16mm
Cutting capacity max.	43mm (bevel 0°)
Cutting capacity max.	27mm (bevel 45°)



Features
- Safety switch
- Induction motor
- Adjustable table 0-45°
- Mountable to workbench
- Parallel/mitre guide
- 2m cable

Includes	TCT saw blade 200x16mm T24 - Wrench - Mitre guide - Parallel guide - Push stick
Optional Accessories	Saw blade 200mm MSA1021 (24T) - MSA1022 (40T)
Availability	Ex-works + FOB

TABLE SAW
1800W - 250MM TSM1033

Specifications

Mains voltage	230-240V~, 50Hz
Input power	1.800W
No load speed	4.700/min.
Saw blade adjustment	0-45°
Max. cutting capacity	0° 74mm - 45° 63mm
Saw blade diameter	250mm
Table height	865mm
Table size (fully extended)	930x625mm



Features
- Safety switch
- Overload protection
- Dust extraction
- Extendable aluminum table top
- Height adjustable saw blade
- Angle adjustable saw blade

Includes	TCT saw blade 250x30mm T40 - Wrench - Hexagonal key - Mitre guide - Parallel guide - Push stick - 4 rubber feet - 2 tilt prevention frames - Safety glasses - Ear plugs
Optional Accessories	Saw blade 250mm MSA1026 (40T) - MSA1027 (72T)
Availability	Ex-works + FOB

TILE CUTTER
600W - 180MM TCM1010

Specifications

Mains voltage	230V~, 50Hz
Input power	600W
No load speed	2.950/min.
Table adjustment	0-45°
Table size	360x330mm
Disc diameter	180mm
Saw blade bore	22.2mm



Features
- Safety switch
- Adjustable table from 0-45°
- Durable chrome plated table
- Parallel / mitre guide
- Low noise induction motor
- Water cooling
- Mountable to workbench

Includes	Diamond saw blade 180x22.2mm - Wrench - Parallel guide - Water tray - Safety glasses - Ear plugs
Optional Accessories	Diamond disc 180mm TCA1004
Availability	Ex-works + FOB

TILE CUTTER
900W - 200MM TCM1011

Specifications

Mains voltage	230V~, 50Hz
Input power	900W
No load speed	2.950/min.
Table adjustment	0-45°
Table size	500x400mm
Disc diameter	200mm
Saw blade bore	25.4mm



Features
- Safety switch
- Adjustable table from 0-45°
- Durable chrome plated table
- Parallel / mitre guide
- Low noise induction motor
- Water cooling
- Mountable to workbench

Includes	Diamond saw blade 200x25.4mm - Wrench - Parallel guide - Water tray - Safety glasses - Ear plugs
Availability	Ex-works + FOB

ARC WELDER
40 - 100A WEM1042

Specifications

Mains voltage	230V~, 50Hz
Welding current	40-100A
Electrode thickness	1.6-2.5mm
Welding cable	2.1m
Earth cable	1.5m



Features
- Current indicator
- Thermal cut-out with control lamp
- Forced cooling

Includes	Welding mask - Scaling hammer/ Steel-wire brush - Quick instruction card
Optional Accessories	Electrodes 12pcs WEA1016 (2mm) - WEA1017 (2.6mm) - Electrodes 1kg WEA1011 (2mm) - WEA1012 (2.6mm) - Electrodes 5kg WEA1014 (2.6mm)
Availability	Ex-works + FOB

ARC WELDER
55 - 160A WEM1035

Specifications

Mains voltage	230/400V~, 50Hz
Welding current	400V max. 160A 230V max. 140A
Electrode thickness	2.0-4.0mm
Welding cable	2.1m
Earth cable	1.5m



Features
- Current indicator
- Thermal cut-out with control lamp
- Suitable for use with either 230V~ or 400V~
- Forced cooling

Includes	Welding mask - Scaling hammer/ Steel-wire brush - Quick instruction card
Optional Accessories	Electrodes 12pcs WEA1016 (2mm) - WEA1017 (2.6mm) - WEA1018 (3.2mm) - Electrodes 1kg WEA1011 (2mm) - WEA1012 (2.6mm) - WEA1013 (3.2mm) - Electrodes 5kg WEA1014 (2.6mm) - WEA1015 (3.2mm)
Availability	Ex-works + FOB

BATTERY CHARGER
6V / 12V BCM1021

Specifications

Mains voltage	230V~, 50Hz
Power Input	Max. 110W
Battery capacity	Min. 20Ah Max. 75Ah



Features
- Ampere meter
- 6/12V charging

Includes	Set battery clamps - 10A fuse
Availability	Ex-works + FOB

BATTERY CHARGER
6V / 12V BCM1020

Specifications

Mains voltage	230V~, 50Hz
Power Input	Max. 400W
Fast charge	12V DC, 12A 100S 6A 180S
Normal charge	6/12V DC, 2A



Features
- Transport handle
- Fast and normal charge
- Deep cycle
- LCD display and indicator
- Reverse polarity, short circuit and overload protection
- Recharge of drained batteries

Includes	Set battery clamps - 80A fuse
Availability	Ex-works + FOB

TROLLY JACK KIT
MAX. 2000KG TJM1008

Specifications

Max. lifting capacity	2.000kg
Min. height	135mm
Max. height	356mm
Lifting height	221mm



Features
- Solid construction with integrated safety valve against overloading
- Control release system
- Two ball bearing castors
- Carrying handle
- Storage case

Availability	Ex-works + FOB

ELECTRIC LEVER HOIST
500W LHM1011

Specifications

Mains voltage	230V~, 50Hz
Power input	500W
Rated load with pulley	250 kg
Rated load without pulley	125 kg
Lifting height with pulley	6m
Lifting height without pulley	12m
Lifting speed with pulley	4m/min.
Lifting height without pulley	8m/min.



Features
- High lifting capacity
- Long lifting cable
- Non rotating steel rope
- Remote control equipped with safety switch

Includes	Mounting brackets - Load hooks
Availability	Ex-works + FOB

PLATFORM TRUCK
MAX. 150KG TTM1027

Specifications

Max. carrying capacity	150kg
Platform dimensions	734x480mm 2 Swivel wheels 2 Fixed wheels



Features
- Rubber wheels
- Foldable push bar
- Large plateau

Availability	Ex-works + FOB

HAND TRUCK
MAX. 225KG TTM1028

Specifications

Max. carrying capacity	225kg
Size	1.130x545x430mm
Lifting plate thickness	3.5mm



Features
- Ball bearing wheels with inflatable tyres
- Stable base plate
- Steel rims

Includes	Availability Ex-works + FOB

PORTABLE COMPRESSOR
1100W CRM1049

Specifications

Mains voltage	230V~, 50Hz
Power input	1.100W (S3-15%)
No load speed	3.550/min.
Air displacement	180 liter/min.



Features
- Oil free
- 3m Rubber hose with universal quick coupling
- Carrying handle with soft grip
- 5m cable

Includes	Tyre inflator with manometer - Blow gun nozzle - 3 Adapters
Availability	Ex-works + FOB

OIL LUBRICATED COMPRESSOR
1.1HP - 750W - 8L CRM1044

Specifications

Mains voltage	230V~, 50Hz
Power input	750W-1.1HP
Tank capacity	8L
No load speed	2.850/min.
Air displacement	118 liter/min.



Features
- Powerful single cylinder pump
- Pressure adjustment from 0-8 bar
- Silent direct drive induction motor
- Universal ¼" quick coupling
- 2 Manometers for tank and outlet pressure

Includes	Oil
Optional Accessories	Air accessory set 6pcs ATA1025 Coiled hose 5m + couplings ATA1026 Air hose 10m + coupling ATA1027 Hose reel 9m ATA1033
Availability	FOB

OIL LUBRICATED COMPRESSOR
1.5HP - 1100W - 24L CRM1045

Specifications

Mains voltage	230V~, 50Hz
Power input	1100W-1.5HP
Tank capacity	24L
No load speed	2.850/min.
Air displacement	155 liter/min.



Features
- Powerful single cylinder pump
- Pressure adjustment from 0-8 bar
- Silent direct drive induction motor
- Universal ¼" quick coupling
- 2 Manometers for tank and outlet pressure

Includes	Oil
Optional Accessories	Air accessory set 6pcs ATA1025 Coiled hose 5m + couplings ATA1026 Air hose 10m + coupling ATA1027 Hose reel 9m ATA1033
Availability	Ex-works + FOB

OIL LUBRICATED COMPRESSOR
2HP - 1500W - 50L CRM1046

Specifications

Mains voltage	230V~, 50Hz
Power input	1.500W-2HP
Tank capacity	50L
No load speed	2.850/min.
Air displacement	206 liter/min.



Features
- Powerful single cylinder pump
- Pressure adjustment from 0-8 bar
- Silent direct drive induction motor
- Universal ¼" quick coupling
- 2 Manometers for tank and outlet pressure

Includes	Oil
Optional Accessories	Air accessory set 6pcs ATA1025 Coiled hose 5m + couplings ATA1026 Air hose 10m + coupling ATA1027 Hose reel 9m ATA1033
Availability	FOB

COMPRESSOR HOSE REEL
ATA1033

Specifications

Outlet	9m hose
Operating pressure	8 bar



Includes	DIN coupling - Orion coupling
Availability	Ex-works + FOB

AIR TOOL SET, 5PCS
ATM1036

Specifications

Spray gun
- Operating pressure 4.5-6 bar
- Container capacity 400 cc

Tyre inflator with pressure gauge
- Operating pressure 0-7 bar

Air blow gun
- Recommended pressure 2-4 bar

Cleaning gun
- Recommended pressure 2-4 bar

5m Coiled hose
- Connection universal / DIN



Availability	Ex-works + FOB

PAINT SPRAY GUN
ATM1039

Specifications

Operating pressure	4.5-6 bar
Container capacity	400 cc



Includes	DIN coupling - Orion coupling
Availability	Ex-works + FOB

TYRE INFLATOR
ATM1041

Specifications

Operating pressure	0-8 bar



Includes	DIN coupling - Orion coupling
Availability	Ex-works + FOB

PAINT SPRAY GUN
ATM1040

Specifications

Operating pressure	4.5-6 bar
Container capacity	750 cc



Includes	DIN coupling - Orion coupling
Availability	Ex-works + FOB

AIR BLOW GUN
ATM1050

Specifications

Recommended pressure	2-4 bar



Includes	Long nozzle - Short nozzle - DIN coupling - Orion coupling
Availability	Ex-works + FOB

AIR NAILER/STAPLER
ATM1051

Specifications

Operating pressure	4-7 bar
Staple length	16-40mm gauge 18
Staple width	5.7mm
Nail length	15-50mm gauge 18
Staple capacity	100 pcs



Includes	Oil - 100 staples 40mm - 100 nails 20mm - 100 nails 30mm - 100 nails 50mm - 2 hex keys - DIN coupling - Orion coupling - Storage case
Optional Accessories	Staples ATA1029 (1300pcs - 18mm) - ATA1030 (1100pcs - 22mm) - ATA1031 (1000pcs - 25mm) Nails ATA1086 (1000pcs - 20mm) - ATA1087 (1000pcs - 30mm) - ATA1088 (1000pcs - 50mm)
Availability	Ex-works + FOB

IMPACT WRENCH
ATM1043

Specifications

Operating pressure	6.3 bar
No load speed	7.000/min
Bolt size capacity	16mm
Max. torque	310Nm
Drive shaft	½" square



Includes	10 Air sockets - 5" Extension bar - Oil - HEX wrench - Nipple - Mini oiler - DIN coupling - Orion coupling - Storage case
Availability	Ex-works + FOB

HIGH PRESSURE CLEANER
1400W GRM1022

Specifications

Mains voltage	220-240V~, 50/60Hz
Power input	1400W
Max. pressure	110 bar
Max. waterflow	390 l/h



Features
- Aluminium pump
- Auto stop system
- Accessory storage facility
- 5m water outlet hose
- 5m power cable

Includes	Spray gun - Adjustable spray lance - Turbo lance - Lance extension - Water inlet adapter with filter - Water connector - Cleaning pin
Optional Accessories	Brush GRA1001, Rotary brush GRA1002
Availability	FOB

HIGH PRESSURE CLEANER
1900W GRM1023

Specifications

Mains voltage	220-240V~, 50Hz
Power input	1900W
Max. pressure	140 bar
Max. waterflow	390 l/h



Features
- Induction motor
- Aluminium pump
- Auto stop system
- Accessory storage facility
- 5m water outlet hose
- 5m power cable

Includes	Spray gun - Adjustable spray lance - Turbo lance - Water inlet adapter with filter - Cleaning pin
Availability	FOB

HIGH PRESSURE CLEANER
2500W GRM1024

Specifications

Mains voltage	220-240V~, 50Hz
Power input	2500W
Max. pressure	160 bar
Max. waterflow	420 l/h



Features
- Induction motor
- Aluminium pump
- Auto stop system
- Build in detergent tank
- Detergent rate adjustment knob
- Accessory storage facility
- 5m water outlet hose
- 5m power cable

Includes	Spray gun - Adjustable spray lance - Turbo lance - Water inlet adapter with filter
Availability	FOB

HIGH PRESSURE CLEANER
1800W GRM1025

Specifications

Mains voltage	220-240V~, 50/60Hz
Power input	1800W
Max. pressure	130 bar
Max. waterflow	420 l/h



Features
- Aluminium pump
- Auto stop system
- Build in detergent tank
- Accessory storage facility
- 5m water outlet hose
- 5m power cable

Includes	Spray gun - Adjustable spray lance - Water inlet adapter with filter - Water connector - Cleaning pin
Availability	FOB

HIGH PRESSURE CLEANER
2200W GRM1026

Specifications

Mains voltage	220-240V~, 50/60Hz
Power input	2200W
Max. pressure	170 bar
Max. waterflow	420 l/h



Features
- Aluminium pump
- Auto stop system
- Build in detergent tank
- Detergent rate adjustment knob
- Accessory storage facility
- 5m water outlet hose
- 5m power cable

Includes	Spray gun - Adjustable spray lance - Water inlet adapter with filter - Cleaning pin
Availability	FOB

CORDLESS LEAF BLOWER
20V - 2.0AH LBM1010

Specifications

Mains voltage (charger)	220-240V~, 50/60Hz
Power input	20V-2.0Ah
No load speed	13.000/min.
Max. Air Velocity	180 km/h
Charging time	1 hour



Features
- Cordless, Li-ion technology
- Soft grip

Includes	Li-Ion battery (20V-2.0Ah) - Charger
Optional Accessories	Battery CDA1106
Availability	FOB

CORDLESS HEDGE TRIMMER
20V - 2.0AH HTM1002

Specifications

Mains voltage (charger)	220-240V~, 50/60Hz
Power input	20V-2.0Ah
No load speed	1.400/min.
Blade length	580mm
Cutting length	520 mm
Cutting width	12.7 mm
Charging time	1 hour



Features
- Cordless, Li-ion technology
- Dual action safety switch
- Soft grip

Includes	Li-Ion battery (20V-2.0Ah) – Charger
Optional Accessories	Battery CDA1106
Availability	FOB

GRASS TRIMMER
350W - 250MM GTM1002

Specifications

Mains voltage	230V~, 50Hz
Power input	350W
Cutting width	250mm
No load speed	11500/min
Wire diameter	Ø1.2mm
Wire length	6m



Features
- Tap and go cutting system
- Working height adjustable
- Cable strain relief

Includes	Wire spool 1.2mm x 6m
Optional Accessories	Wire spool 1.2mm x 6m GTA1001
Availability	FOB

GRASS TRIMMER
20V - 2.0AH GTM1003

Specifications

Mains voltage (charger)	220-240V~, 50/60Hz
Power input	20V-2.0Ah
No load speed	8.000/min.
Wire diameter	Ø1.2mm
Wire length	5m
Charging time	1 hour



Features
- Cordless, Li-ion technology
- Tap and go cutting system
- Working height adjustable
- Working angle adjustable
- Soft grip

Includes	Li-Ion battery (20V-2.0Ah) – Side wheel – Charger - Wire spool 1.2mm x 5m
Optional Accessories	Wire spool 1.2mm x 5m GTA1002
Availability	FOB

ACCESSORIES

AIR ACCESSORY SET 6 PCS
ATA1025
For CRM1044, CRM1045 and CRM1046




COILED HOSE 5M + COUPLINGS
ATA1026
For CRM1044, CRM1045 and CRM1046



AIR HOSE 10M + COUPLINGS
ATA1027
For CRM1044, CRM1045 and CRM1046



STAPLES 12MM 1.800 PCS
ATA1028
For ATM1042



STAPLES 18MM 1.300 PCS
ATA1029
For ATM1042 and ATM1051



STAPLES 22MM 1.100 PCS
ATA1030
For ATM1042 and ATM1051



STAPLES 25MM 1.000 PCS
ATA1031
For ATM1042 and ATM1051



STAPLES 30MM 1.000 PCS
ATA1048
For ATM1051



STAPLES 40MM 1.000 PCS
ATA1049
For ATM1051



STEEL NAILS 20MM 1.000 PCS
ATA1086
For ATM1044 and ATM1051




STEEL NAILS 30MM 1.000 PCS
ATA1087
For ATM1044 and ATM1051




STEEL NAILS 50MM 1.000 PCS
ATA1088
For ATM1044 and ATM1051




GRINDING STONE 150X16X12 7MM P36 GREY
BGA1053
For BGM1019



GRINDING STONE 150X16X12 7MM P60 GREY
BGA1054
For BGM1019




GRINDING STONE 150X20X12 7MM P36 GREY
BGA1055
For BGM1020 and BGM1021



GRINDING STONE 150X40X12 7MM P80 WHITE
BGA1056
For BGM1020



GRINDING STONE 200X40X20MM WET USE
BGA1057
For BGM1021



POLISH SET 180MM 5 PCS
AGA1023
For AGM1084P and AGM1120P




ACCESSORIES

SANDING DISC SET 2X P80 3X P120 180MM
AGA1022
For AGM1084P and AGM1120P



SANDING PAPER SET 225MM 5X P60, 5X P120, 5X P180, 5X P240, 5X P400
DSA1001
For DSM1010



SANDING DISC SET 2X P60 5X P100, 3X P150 150MM
BGA1036
For BGM1003



SANDING DISC SET P100 10 PCS 150MM
BGA1037
For BGM1003



SANDING DISC SET P150 10 PCS 150MM
BGA1038
For BGM1003




SANDING DISC SET P60 P100 P150, 10 PCS 150MM
BGA1039
For BGM1003




SANDING DISC SET 2X P60 5X P100, 3X P150 150MM
BGA1062
For BGM1022




SANDING BELT SET P60 P100 P150, 3 PCS 915X100MM
BGA1058
For BGM1003 and BGM1022



SANDING BELT SET P100 3 PCS 915X100MM
BGA1060
For BGM1003 and BGM1022



SANDING BELT SET P60 P100 P120, 3 PCS 533X75MM
BSA1013
For BSM1024



BISCUITS 56X23X4MM 50 PCS
BJA1004
For BJM1009

SAW BLADE
BJA1005
For BJM1009



BATTERY 12V - 1.5AH LI-ION
CDA1085
For CDM1118 and CDM1119



BATTERY 18V - 1.5AH LI-ION
CDA1087
For CDM1120 and CDM1131



BATTERY 12V - 1.5AH LI-ION
CDA1094
For JSM1026, OTM1006, CTM1016



BATTERY 18V - 4.0AH LI-ION
CDA1096
For CDM1127



BATTERY 20V - 2.0AH LI-ION
CDA1106
For GTM1003, HTM1002, LBM1010



BATTERY 20V - 2.0AH LI-ION
CDA1130
For CDM1138



BATTERY 16V - 1.5AH LI-ION
CDA1140
For CDM1139



BATTERY 12V - 1.5AH
CDA1142
For CDM1118, CDM1119, CDM1129




BATTERY 18V - 1.5AH LI-ION
CDA1144
For CDM1120



ACCESSORIES

GUIDE RAIL SET
CSA1049
For CSM1043



COMBITOOL SET 100 PCS
CTA1007
For CTM1010, CTM1012, CTM1016 and CTM1017



COMBITOOL SET 40 PCS
CTA1008
For CTM1010, CTM1012, CTM1016 and CTM1017



SAW BLADE 185MM 24T
CSA1007
For CSM1039



SAW BLADE 200X30/16 24T
MSA1021
For TSM1032 and TSM1036



SAW BLADE 200X30/16 40T
MSA1022
For TSM1032 and TSM1036



SAW BLADE 210X30/16/18 24T
MSA1024
For MSM1035, MSM1037, MSM1039 and TSM1035



SAW BLADE 210X30/16/18 40T
MSA1025
For MSM1035, MSM1037, MSM1039 and TSM1035



SAW BLADE 250X30/16 40T
MSA1026
For TSM1033



SAW BLADE 250X30/16 72T
MSA1027
For TSM1033



SAW BLADE 255X30/16 40T
MSA1028
For MSM1038



SAW BLADE 255X30/16 72T
MSA1029
For MSM1038



PRECISION SAW BLADE 85X15 DIAMOND
CSA1046
For CSM1043



PRECISION SAW BLADE 85X15 24T (TCT)
CSA1047
For CSM1043



PRECISION SAW BLADE 85X15 44T (HSS)
CSA1048
For CSM1043




SANDING BELT SET 10MM 8 PCS, 2X P40, 3X P80, 3X P120
EFA1003
For EFM1001




SANDING BELT SET 13MM 8 PCS, 2X P40, 3X P80, 3X P120
EFA1004
For EFM1001



STAPLES 8MM 2000 PCS U-SHAPE
ETA1009
For ETM1004, ETM1005




STAPLES 10MM 2000 PCS U-SHAPE
ETA1013
For ETM1004, ETM1005




ACCESSORIES

STAPLES 12MM 2000 PCS U-SHAPE
ETA1014
For ETM1004, ETM1005



STAPLES 14MM 2000 PCS U-SHAPE
ETA1010
For ETM1004



GLUE STICKS 11.2X100MM 6 PCS
GGA1002
For GGM1002



GLUE STICKS 7X150MM 6 PCS
GGA1003
For GGM1003



GLUE STICKS 11.2X150MM 12 PCS
GGA1005
For GGM1004



SANDING PAD
OTA1003
For OTM1005 and OTM1006



HSS SEGMENT SAW BLADE
OTA1004
For OTM1005 and OTM1006



CARBIDE BLADE
OTA1005
For OTM1005 and OTM1006



MULTITOOL ACCESSORY SET 4 PCS
OTA1007
For OTM1005, OTM1006, OTM1007 and OTM1009



BRUSH
GRA1001
For GRM1022 and GRM1031

Availability FOB



ROTARY BRUSH
GRA1002
For GRM1022 and GRM1031

Availability FOB



WIRE SPOOL 1.2MMX6M
GTA1001
For GTM1002



WIRE SPOOL 1.2MMX5M
GTA1002
For GTM1003



PLUNGE CUTTING BLADE
OTA1001
For OTM1005 and OTM1006



SCRAPING KNIFE
OTA1002
For OTM1005 and OTM1006



WHISK 120X680MM
PMA1004
For PMM1006 and PMM1010



WHISK 140X600MM TWO-PART
PMA1008
For PMM1006 and PMM1010



ROUTER BITS SET 20 PCS
PRA1008
For PRM1015 and PRM1021



ACCESSORIES

CHISEL SET 82MM 2 PCS
PPA1003
For PPM1010



SANDING PAPER SET P80 5 PCS
PSA1007
For PSM1013



SANDING PAPER SET P120 5 PCS
PSA1008
For PSM1013



SANDING PAPER SET P60, P80, P120, 5 PCS
PSA1031
For PSM1024



SANDING PAPER SET P80 10 PCS
PSA1033
For DSM1009 and OTM1005



SANDING PAPER SET P120 10 PCS
PSA1034
For DSM1009 and OTM1005




JIG SAW BLADES 10 PCS
JSA1004
For JSM1014, JSM1023, JSM1026, JSM1030 and JSM1034




SAW BLADES RECIPROCATING SAW 9 PCS
RSA1001
For RSM1019




SCROLL SAW BLADE 15TPI 5 PCS
SSA1001
For SSM1005 and SSM1007



SCROLL SAW BLADE 10TPI 5 PCS
SSA1002
For SSM1005 and SSM1007



SCROLL SAW BLADE 18TPI 5 PCS
SSA1003
For SSM1005 and SSM1007



SCROLL SAW BLADE 25TPI 5 PCS
SSA1004
For SSM1005 and SSM1007




DIAMOND SAW BLADE 180MM
TCA1004
For TCM1010



DIAMOND SAW BLADE 200MM
TCA1006
For TCM1011



ELECTRODES 2.0MM 1 KG
WEA1011
For WEM1035 and WEM1042



ELECTRODES 2.6MM 1 KG
WEA1012
For WEM1035 and WEM1042



ELECTRODES 3.2MM 1 KG
WEA1013
For WEM1035




ELECTRODES 2.6MM 5 KG
WEA1014
For WEM1035 and WEM1042



ELECTRODES 3.2MM 5 KG
WEA1015
For WEM1035




ELECTRODES 2.0MM 12 PCS
WEA1016
For WEM1035 and WEM1042




ACCESSORIES

ELECTRODES 2.6MM 12 PCS
WEA1017
For WEM1035 and WEM1042



ELECTRODES 3.2MM 12 PCS
WEA1018
For WEM1035 and WEM1042



SAW BLADE SET 125MM 2 PCS DIAMOND
WSA1001
For WSM1009



SAW BLADE SET 150MM 2 PCS DIAMOND
WSA1002
For WSM1008



MACHINE VICE
TDA1013
For TDM1025 and TDM1026





WWW.FERM.COM

2002-18